

POWER PRODUCTS
2011-12

# BRITAINS No.1) FOR PROFESSIONAL TO 1969 FOR PROFESSIONAL TO 1969

**QUALITY ASSURED PRODUCTS** All Clarke products comply with the latest British & European Standards & European Safety / CE Marking Directives. They are all thoroughly tested and inspected by our own in House R&D and Q.C. departments. Specialist products are also further tested by an independent 3rd party government approved test house.





# **PRODUCT AWARDS**

Many of our products have won awards from a variety of leading magazines when independently tested and reviewed. You will find product awards throughout the catalogue, these include the following logos.







# HIGH QUALITY PACKAGING

Regarded as the best in our industry, our vast range of stylish full colour packaging distinguishes the product, its features and applications, ensuring a really effective point of sale display for our customers, inspiring even greater faith in our highly successful brand.

# **WORLDWIDE EXPORT & SHIPPING**

Our export department offers a complete service covering selection, packing, insurance and freight to any foreign destination. Our friendly professional team are experienced in dealing with large projects and tight deadlines worldwide.

# STOCK AVAILABILITY

With over 3000 product lines available and over £30 million worth of product in stock, our state of the art picking and despatch system allows products ordered before 2pm to be despatched the same day.





# CONTACT DETAILS

# **SALES HOTLINES**

Tel: 01992 565 333

Fax: 01992 561562

Email: sales@clarkeinternational.com



# **EXPORT HOTLINES**

Tel: 00 44 (0) 1992 565 335

Fax: 00 44 (0)1992 561562

Email: export@clarkeinternational.com



# HEAD OFFICE

Tel: 01992 565 300

Fax: 01992 561562

Web: www.clarkeinternational.com



Tel: 020 8988 7400

Fax: 020 8558 3622

mail: parts@clarkeinternational.com

# **SERVICE HOTLINES**

Tel: 020 8988 7400

Fax: 020 8558 3622

Email: service@clarkeinternational.com





# **CONTENTS**

# SITE TOOLS 4-7

Heavy Duty Tools & Equipment for Tough Daily Site Use

# AIR COMPRESSORS AND TOOLS

Air Compressors, Air hose, Air Tools, Regulators & Accessories

GENERATORS & ELECTRICAL

Halogen Lights, Transformers, Cables, Converters & Inverters

WELDING

Arc, Mig, Tig, Spot Welders, Accessories & Consumables

# GARAGE EQUIPMENT

Trolley Jacks, Engine Cranes, Hydraulic Presses, Start / Chargers

CONSUMABLES

Automotive, Workshop and Janitorial

## MATERIALS HANDLING

Pallet, Sack & Platform Trucks, Castors & Lifting Equipment

## TOOL STORAGE

Tool Chests, Cabinets, Racks, Benches, Folding Tables & Site Boxes

## HAND TOOLS

Huge Choice of Socket Sets, Automotive Tools, Drill & Screwdriver Sets

# CONSTRUCTION

Concrete Mixers, Ladders, Chisels & Hammers, Tile Cutters

# **POWER TOOLS**

Drills, Angle Grinders, Discs, Sanders & Planers, Staple Guns

# **MEASURING TOOLS**

Vernier Callipers, Micrometers & Punches

## METALWORKING

Lathes, Bench Grinders, Vices, Pillar drills, Bandsaws

# WOODWORKING

Lathes, Table & Mitre Saws, Sanders, Bandsaws & Planers

GARDEN EQUIPMENT Tarpaulins, Log Splitter, Garden Trolleys, Sprayers

VENTILATION

Fans, Ventilators & Air Conditioners

## HEATING

Space Heaters, Electrical Fan & Infrared Heaters, Cast Iron Stoves & Fireplaces

# OUTDOOR LEISURE

Fruit Press, Binoculars, Spotlights & 2 Way Radios

**SECURITY** 

Safes, Cash Boxes & Key Cabinets

# INDEX

Full Alphabetical Index

Every effort has been made to ensure that the information in this catalogue is correct. However, we reserve the right to introduce changes without prior notice. E&OE.

40 - 50

8 - 39

51 - 60

61 - 82

84 - 92

93 - 111

112 - 154

155 - 160

161 - 173

174 - 176

177 - 187

188 - 195

WATER PUMPS & POWER WASHERS 196 - 209 Electric & Engine Driven Pumps, Electric & Engine Driven Power Washers

210 - 215

216 - 217

218 - 225

226 - 228

238 - 241



# 🚺 & 🕗 Top Quality Cast Iron And Steel Stoves

Part of our great NEW range (see page 221) These great looking contemporary stoves provide a modern look, whilst creating warmth and ambience within your room. Features include: Dealt to comply with the latest EN13240 standard (Mayfair and Majestic are also CE compliant) Dop and rear outlets. Air control for altering burn rate/heat output. Top quality heat resistant glass and an air wash system to keep the glass clean, maximising the view of the flame.



# 🚺 Majestic Cast Iron Stove

This superb looking stove with heat output up to an impressive 14Kw can be used for burning wood or coal and includes a riddling grate for easy ash collection.



# 🔼 Stainless Steel, Twin Wall Flue Pipes

Ideal for both indoor and outdoor use. This great looking, top quality flue is approved to BS 4543 Parts 2&3 and contains a 316 Grade stainless inner, a 25mm high density core and a 304 grade stainless outer > 520-920mm adjustable

ladder is light to carry & compact to store.
150kg Extends to 3.8
. DO ENIGOS . I I

Ladder - TL-3

Ideal for tradesmen & DIY this great new , easy to transport Max working load 81m Manufactured to BS EN131 standards Doverall Dims (LxWxH): Closed: 506 x 86 x 1030mm, Extended: 506 x 86 x 3805mm





See Page

221

Majestic

695

442

The new mayfair, with it's superb build quality, is our first steel stove, additional features include: Vermiculite fire brick lining

Mayfair Steel Stove

Model

Width mm

Depth mm



Part No. 6462108

ြ MGH1



# MGH1 Mobile Gas Heater

- Compact, mobile heater for instant warmth in the home, office, workshop etc > 3 heat output settings; 1.55kW, 2.9kW, 4.2kW Flame failure device Anti tilt switch
- Inc. hose & regulator
- ▶ Requires 15kg butane cylinder (not included)
- 4 castors for easy movement.

Part No. 6920021

# 6 720w Petrol Generator - G720

- Portable, compact & lightweight
- Overload circuit breaker
- Ideal for caravanning, camping, boating & emergency home use
- 720w maximum power output
- 12v battery charging facility
- Air cooled 2 stroke engine
- ▶ 5.8 running hours @ <sup>3</sup>/<sub>4</sub> load
- 230v AC (13 amp) socket
- Anti-vibration rubber feet, carry handle & recoil starter
- Weight 17kg
- Dims (LxWxH): 380x312x362mm. Part No. 8857800



ADOL

Mayfair

562

472









3.39kg

6480210

Hammer Drill with Drill Bits - CHD1050 General drilling & masonry drilling with optional hammer action. Two speed. Blows Per Min -

Speed 1: 0-1920, Speed 2: 0-4480.

Complete with assorted titanium coated bits including

Masonry bits: 6, 8, 10mm Wood

bits: 5, 6, 8mm and Metal bits: 4.5, 5, 6mm. Robust construction with soft rubber grip. > Side handle. Carry case with handle.

**Includes Drill Bits** For Masonry, Wood,

Metal & Carry Case

🔼 Professional Variable Speed 1/2" Router With 15pc Router Bit Set - CR2

Powerful heavy duty machine ideal for trade use. ▶ Soft start. ▶ Variable speed control.

▶ Micro depth adjustment. ▶ Depth and spindle lock feature. Dust extraction outlet. Durable carry case.

Two guide rods, 16 & 30mm guide bushes, parallel & circular guides. 15 piece router bit set in wooden box.



No. load speed 7,400-21,600 rpm Max. plunge depth 60mm Collet Size (inches) 1/4",3/8", 1/2" Motor 2100w (230v)

Weight 6.5kg 6462075 Part No.

Includes 15 pc router bit set

CHD1050



# 230mm (9") Contractor Angle Grinder - CON2600

With the most powerful motor in our range of angle grinders, this professional, heavy duty 'Contractor' is ideal for cutting, grinding, polishing and sanding. 2600 Watt, 230v motor 230mm (9") disc diameter ) 6000rpm no-load disc speed ) M14/22mm

threaded drive spindle ) Spindle lock facility

right sides. Includes disc guard and spindle

No Load Speed 11,000rpm. Weight 2.7kg.

lock. Spindle thread/Bore M14/22mm.

7.32kg

6482015

115mm (4½") Professional Angle Grinder

Weight

Part No.

- CON115

Professional grinder,

suitable for use with abrasive metal cutting, grinding and diamond discs. Supplied with abrasive metal cutting disc and kit box.

Powerful 1010w motor (230v). ▶ Integral rubber strip on handle for a secure grip and user

comfort.

Safety Switch.

▶ Handle can be

Part No. 6470140.

fitted to top, left or





(3) CON115

Handle Rotates 90 \_eft And Right



Trade quality circular saw fitted with an adjustable rip fence with measuring scale. Depth gauge and bevel cutting facility. Supplied with a TCT blade.

▶ Safety lock switch. ▶ Input Power 1300w, 230v. No Load Speed 4800rpm. Max Cut Depth 90°/45° 60/45mm.

Blade/Bore dia. 185/20mm.

TCT Saw Blade Type. With dust extraction and bevel capacity.

Comes with kit box

Weight 6kg. Part No. 6462040.

🜀 CCS-2





# 小月: ⅓: (中





# Contractor Wall Chaser - CON1450WC

Cuts clean channels into plaster, brick, thermalite block, concrete etc. for laying electric cables. Saves time and effort whilst providing accuracy. Ideal for electricians and plumbers. Can also be used for DIY, Adjustable

cutting depth and width to suit various applications 2 Diamond Blades

Break out chisel for clearing debris leaving clean channels ▶ Soft Start

▶ Spindle lock

Dust extraction facility.

Part No. 6462165

Power (in watts)	1450w
Voltage	230v
Spindle Thread	M14
Disc Diameter	150mm
Cutting width	8-30mm
Cutting depth	8-40mm

CON1450WC

**Supplied With Handy Carry** Case, Side Handle, Chisel And Twin Diamond Blades

# Professional Biscuit Jointer - BJ600

This professional woodworking jointer cuts grooves for biscuit joint connections quickly and accurately. Ideal for forming joints for picture frames, drawers, book shelves, table tops etc.

Supplied with 100mm (4") TCT Blade. Comfortable hand grip. Dust

collection bag. It High quality cast alloy front with a chrome steel plate.



**DIY/PRO Biscuit Jointer BJ300** See Page 167

Model BJ600 Input power 600w No load speed (rpm) 10000 Cutter diameter 100mm Max cutting depth 16mm Fence adjustment 0-90° **Dust extraction** Kit box 3kg Weight Part No. 6462003

# Multi-Purpose 5" (125mm) Twin Blade Saw - TS125 Compact & lightweight, cuts through woods, plastics & metals with ease Twin counter-rotating blades minimise kickback, sparks and overheating Produces a single cut and leaves a clean burr-free finish Motor: 230v, 650w Cutting depth: 33mm Inc. 2 x TCT blades, 6 x lubricating sticks, side handle & box wrench with pin & tough moulded carry case. Part No. 6462047 **2** TS125 **TWIN BLADE**

# Contractor ½ Sheet Orbital Sander - CON300

Variable speed sander ideal for trade use

See Page 161 For Full Details

Trigger lock & comfort grips for reduced fatigue

Quick change sheet clamp

Special pad design for greater dust extraction


Six variable speeds (1) CON300

330w input power

230x115mm sanding plates Includes 10 sanding sheets

No Load speed 6000-11000 rpm.

Part No. 6462052.



# 6 150mm Random Orbital Sander - CROS2

For fast removal of paint or for fine swirl-free finishing.

▶ Hook & loop style sanding discs & plate.

▶ Twin comfort grip handles. ▶ Lock on trigger.

Inc. dust bag & 6 sanding discs. Input Power 750w.

▶ Variable speed. ▶ 150mm sanding plates. ▶ 4000-7000 rpm Speed.

Dust extraction & kit box Part No. 6462011.







Includes Tough

Rubber Tyres

Amazing value for money, these extra tough all steel mixers fold for easy transportation & storage.

Includes protective guard on ring gear.

Fitted with rubber tyres for easy movement over uneven ground.

125 litre mixing capacity

CCM125C

Compact mixer, Folds for Easy ideal for smaller Transportation scale projects by either trade or DIY.



Legs Fold for Storage & **Transportation**  CCM50

Rubber

Tyres

			_			
	Model	Mixing Cap.	Voltage	Motor	Weight	Part No.
0	CCM125C	125ltr	230v	1/3 hp	69kg	3400840
	CCM126	125ltr	110v	1/3 hp	69kg	3400842
2	CCM50	30ltr	230v	1/6 hp	40kg	3400850



Our top selling CSV pumps are also available in 110 volt, ideal for site use. Suitable for clean and dirty water including solids upto 30mm.

- ▶ Tough corrosion & rust proof materials.
- Long life ceramic shaft for reliability.
- ▶ Efficient water cooling for long term operation.
- Overload protection.



Pumps Solids up to 30mm



Built for tough daily use by garages, fleet operators, plant hirers, contractors etc.

▶ Robust 6.5hp Honda petrol engine. ▶ Max pressure 150bar/2175psi. Max flow 11 ltr/min. Highly efficient direct drive. Big heavy duty pneumatic tyres for easy mobility.

Adjustable high pressure output and twin lance.

Dimensions (LxWxH) 750x455x800mm.

Weight 41kg. Part No. 7330282.

> 150bar 2175psi **Pressure**

Includes Detergent Facility

PLS160Y

POWERED by HONDA

Model	Outlet	Pump	Motor	Max. Flow	Max.	Weight	Part
	Inches	Type	Watts	LPM	Head M	kg	No.
3 CSV1A (110V)	11/2"	Dirty Water	330	118	5	3.7	7230582
CSV2A (110V)	11/2"	Dirty Water	620	200	8	5.2	7230602

# 5 & 6 Industrial Petrol **Engine Air Compressors** - PP15YB & PPH15YB

First choice for plant hire, construction sites, service yards, mobile maintenance crews etc.

- Genuine 6.5hp Honda petrol engine.
- ▶ 50 litre receiver. ▶ Twin cylinder pump.
- ▶ 15 cfm displacement. ▶ Cast iron cylinder for longer life and greater efficiency.
- Fitted filter/regulator. Pressure unloading genie. Heavy duty, for years of reliable use.

Fully painted for lasting protection and durability.



	Model	Description	Dims. (LxWxH) mm	Weight	Part No.
6	PP15YB	Fitted handle	1000x490x780	60kg	2091005
6	PPH15YB*	Full frame	1100x400x780	63kg	2091010

\* 'H' models are fitted with protective steel frames for full protection on site and for hire use.











**3** CC190

CHAPTER CONTRACTOR

# 🕦 - 🐠 Professional Tool Chests & Cabinets

Professional heavy duty tool chests & cabinet for tough daily use in industrial workshops.

- Reinforced extra heavy gauge double wall steel construction. Indented end and base for extra strength & rigidity. Dafety pushlock drawer design prevents drawers from opening accidentally. Dall bearing drawer runners for smooth sliding action. > Tough powder coated protective finish.
- Protective anti-slip drawer liners and cabinet top mat. CC229 has twin gas struts to support lid. Nickel chrome plated aluminium drawer handles on chests.
- Chrome plated handle on cabinets.
- Locking mechanism. Inserts for drawer identification. Full length piano hinge lid for smooth opening, security & strength.
- Cabinets are fitted with 5" industrial castor wheels - 2 with brake.



See Also Full Range of Red, Blue and Black Tool Chests and Cabinets on pages 100-105

Model	Description	Max. drawer load kg	Weight (kg)	Dimensions (LxWxH) mm	Part No.
① CC22	21 Drawer Tool Chest	36	54.2	1032x405x485	7631064
② CC226	16 Drawer Mobile Cabine	et 38	120	1045x461x1010	7636208
€ CC10	9 Draw Tool Chest	38	27	666x305x375	7631060
<b>4</b> CC170	7 Drawer Tool Cabinet	43	52	675x465x1000	7631062

## **Heavy Duty Site Storage**

Site boxes designed for the storage & protection of power tools and equipment. Ideal for on site use and in vans, workshops, garages, etc.

▶ Heavy gauge steel construction. ▶ Reinforced base section for strength. Fully phosphated & powder coated.

## Site Box - CSB25

Provide large storage space on site.

Fitted with large side handles to ease transportation. Recessed padlock mount for resistance to vandals. (padlock not included)

# Heavy Duty Site Box - CSB85

Thick steel construction for extra protection of contents.

- ▶ Full length piano hinge ▶ 2 external padlock mounts (padlocks not supplied) Tough powder coated finish for weather resistance Strong carry handles to ease transportation
- Fork lift/pallet truck insertion points to ease manoeuvrability

# 🚺 Extra Large Site Box - CSB100

Huge storage capacity.

Recessed twin deep shackle padlock mounts, for vandal resistance (padlocks not included). Delearance underneath for Forklift/Pallet Truck insertion to ease manoeuvrability.

Model	Dims.	Sheet	Weight.	Part
	(LxWxH) mm	thickness	kg	No.
G CSB25	812x492x495	1.5mm	34	7637450
© CSB85	1067x508x895	1.5mm	47	7637470
<b>☑</b> CSB100	1220x615x682	1.5mm	66	7637502



CC170



G CSB25

REED!

Great for Secure Storage of Valuable Hand and Power Tools

# 1 Wiz Mini Air Compressor

Ideal for designers, artists, modellers etc. This compact portable diaphragm air compressor provides oil free air ideal for air brush work.

- Exceptionally light. Maintenance free. Ultra guiet (less than 55db).
- Includes built in carry handle, on/off switch,





High output air compressor & spray kit. This oil-free unit is ideal for DIY and semi professional use. Complete with syphon spraygun with fan control and 3 metres rubber air hose with quick fit couplings.

- Maximum pressure 116 psi / 8 bar.





# Pioneer 220 Air Compressor

Ideal for a wide variety of uses including spraying, stapling and inflating.

▶ Fully automatic stop/start control ▶ Neat, portable design with tubular steel frame which includes wheels and handle for easy movement around the workshop or garage ) Steel frame also makes lifting into a car or van much easier Includes air receiver pressure safety valve and gauge Dutlet air pressure is easy to control with the adjustable regulator and pressure gauge Maximum working pressure 116psi/8 bar Air receiver capacity 10 litres 2hp, 230v motor

Includes Fully Automatic Stop/Start Control





R PIONEER 220

	Displacement	Max.	Motor	Voltage	Dimensions	Weight	Part
Model	cfm	Pressure	hp		LxWxH (mm)	kg	No.
1 Wiz	1.58	40psi/2.8 Bar	0.125	220v	238x131x185	4.5	2310017
2 Monza kit	7.0	116psi/8 Bar	1.5	230v	330x190x290	10.5	2220050
3 Pioneer 220 (230)	<b>V</b> ) 6.5	116psi/8 Bar	2.0	230v	395x320x630	22	2320220
Pioneer 220 (110\	<b>/</b> ) 6.5	116psi/8 Bar	2.0	110v	395x320x630	22	2320221



Ideal for use with our many hobby/semi-professional air compressors. Kit contains: Paint spray gun.

- Recoil hose. Paraffin gun.
- Tyre inflator with gauge. Blow gun. All connections 1/4" BSP.
- Weight 2kg.

Part No. 3110155.





See Page 26 For Airbrushes



1250x460x720 SHHH 7/100 6.5 100 1.37 All units 230v, 1 phase. Check duty cycle when selecting.

9

24

25

50

0.5

0.5

0.92

0.92

310x310x530

400x400x530

580x320x580

980x440x650

2320770

2320800

2320805

2320810

2320850

😉 Synthetic Oil - 1 Litre

For use with our Shhh Air range

of compressors. Part No. 3050795.

27

43

63

86

2.15

2.15

4.5

4.5

**3** SHHH 3/9

SHHH 3/24

SHHH 5/24

SHHH 5/50

# **10** AIR COMPRESSORS

# **Semi-Professional Air Compressors**

# 1 - 4 Ranger Air Compressors

Covering a wide range of DIY/semi professional uses, these superb units incorporate many features demanded by professional users including:

Fully automatic stop/start control.

- Fitted regulator with gauge for controlled air pressure.
- ▶ Wheels and handle for easy mobility. ▶ 8 Bar (116psi) maximum working pressure.





7.8

7.8

2

Ranger 46

2 Ranger 64





24

50

585x285x595

800x350x660

2225060

2225065

21

30





Great value for money, the Hunter range offers high output compressors, ideal for DIY and light trade use including spraying (automotive bodywork, fences, sheds etc.) nailing, stapling, cleaning etc.

RANGER 54

- ▶ Fully automatic stop/start control.
- Fitted regulator with gauge for controlled air pressure.
- All 230v.

Model	Displ. cfm	Receiver Litres	Motor HP	Dimensions LxWxH (mm)	Max Working Pressure (bar)	-	Part No.
Hunter 25	8.7	24	2.5	600x265x580	8 bar	24	2225405
6 Hunter 55	8.7	50	2.5	800x350x680	8 bar	33	2225410



WARRIOR 30A O/F

WARRIOR 60A O/F

OIL FREE

# **Professional & DIY Direct Drive Air Compressors**

# 1 - 4 Warrior 2.0 hp Professional Air Compressors

These professional 2hp units offer great performance for their size. ) 8.7cfm air displacement (8.0cfm on oil free versions) Pressure regulator with gauge Prully automatic stop/start control Robust 2.0hp, 1Ph 230v Motor\* ▶ Wheels & handle for easy movement ▶ Warrior range offers oil free models and air receivers of 24 & 50 Litres



(vvarri	or 30 110	/)				•
Displ.	Receiver	Motor	Dimensions	Max Working	Weight	Part
cfm	Litres	hp	LxWxH (mm)	Pressure (bar/psi)	Kg	No.
8.7	24	2.0	610x302x610	10 bar/145 psi	28	2320300
8.7	24	2.0	610x302x610	10 bar/145 psi	28	2320320
8.7	50	2.0	1053x310x660	10 bar/145 psi	37	2320360
8.0	24	2.0	660x330x630	8 bar/116 psi	23	2320321
8.0	50	2.0	830x350x660	8 bar/116 psi	39	2320361
	Displ. cfm 8.7 8.7 8.7 8.7	Displ. cfm         Receiver Litres           8.7         24           8.7         24           8.7         50           8.0         24	cfm         Litres         hp           8.7         24         2.0           8.7         24         2.0           8.7         50         2.0           8.0         24         2.0	Displ. cfm         Receiver Litres         Motor hp LxWxH (mm)           8.7         24         2.0         610x302x610           8.7         24         2.0         610x302x610           8.7         50         2.0         1053x310x660           8.0         24         2.0         660x330x630	Displ. cfm         Receiver Litres         Motor hp         LxWxH (mm) LxWxH (mm)         Pressure (bar/psi)           8.7         24         2.0         610x302x610         10 bar/145 psi           8.7         24         2.0         610x302x610         10 bar/145 psi           8.7         50         2.0         1053x310x660         10 bar/145 psi           8.0         24         2.0         660x330x630         8 bar/116 psi	Displ. cfm         Receiver Litres         Motor hp         Dimensions LxWxH (mm)         Max Working Pressure (bar/psi)         Kg           8.7         24         2.0         610x302x610         10 bar/145 psi         28           8.7         24         2.0         610x302x610         10 bar/145 psi         28           8.7         50         2.0         1053x310x660         10 bar/145 psi         37           8.0         24         2.0         660x330x630         8 bar/116 psi         23

5 - 6 Rebel 2.5hp Professional Air Compressors

**Built to combine high** performance with reliability in a neat, compact portable design.

- 9cfm air displacement
- 145psi/10 Bar maximum working pressure
- ▶ Fully automatic stop/start control
- Robust 2.5hp, 1Ph 230V Motor\*
- ▶ Pressure regulator with guage
- Wheels & handle for easy movement
- Rebel range offers 24 & 50 litre air receivers



Huge Choice Of Spray Guns See Pages 25-26



**WARRIOR 60** 

\* 110v model available (Rebel 60 110v)

	Displacement	Receiver	Motor	Dimensions	Max Working	Weight	Part
Model	cfm	Litres	hp	LxWxH (mm)	Pressure (bar/psi)	Kg	No.
6 Rebel 30	9.0	24	2.5	660x330x648	10 bar/145 psi	37.0	2320400
6 Rebel 60	9.0	50	2.5	1055x310x700	10 bar/145 psi	43.0	2320410
Rebel 60 110v	9.0	50	2.5	1055x310x700	10 bar/145 psi	43.0	2320420



(5) REBEL 60

# **Professional Air Compressors**

# Portable Direct Drive Air Compressor - PED14A50

Portable Direct Drive V-Twin compressor with a 50 litre tank. Ideal for use with air tools and all commonly used spray equipment.

- ▶ Large 14cfm air displacement ▶ 116 psi/8 bar working pressure
- Fully automatic with fitted regulator and gauge.



# Portable Direct Drive Air Compressor - PED14A100

Portable, direct drive, V-Twin compressor with a large 100 litre tank for extra capacity in bigger workshops.

- ▶ Large 14cfm air displacement ▶ 116 psi / 8 bar working pressure
- ▶ Fully automatic ▶ Fitted with regulator and gauge for controlled air pressure ▶ Handle and wheels for ease of use around the workshop.





# 3 Stationery Direct Drive Air Compressor - SED14A100

Stationary, direct drive, V-Twin compressor with a 100 litre tank makes it ideal for automotive spraying applications.

▶ 14cfm air displacement. ▶ 116 psi/8 bar working pressure. ▶ Fully automatic.

Model	PED14A50	PED14A100	<b>3</b> SED14A100
Voltage	230v, 1ph	230v, 1ph	230v, 1ph
Motor	3HP	3HP	3HP
Air Displacement	14cfm	14cfm	14cfm
Maximum Working Pressure	8 Bar (116 psi)	8 Bar (116 psi)	8 Bar (116 psi)
Air Receiver	50 ltr	100 ltr	100 ltr
Dims (LWH) mm	820x420x740	1100x820x570	1165x420x1050
Weight kg	46kg	60kg	56kg
Part No.	1499200	1499202	1499230
1			

Full Range Of Spray Guns See Page 25



# 4 & 5 Boxer Compressors

100ltr

Receiver

Built for tough, reliable use. These units feature:

- Cast iron twin pump.
- Twin outlet.

SED14A100

Regulator with gauge.

Model 4	BOXER 55	<b>5</b> BOXER 100
Displacement (cfm)	12.2	12.2
Max. Pressure	10 Bar	10 Bar 🥼
Air Receiver	50 Ltr	90 Ltr
Motor hp	3	3
Dims LxWxH (mm)	325x395x715	1220x460x810
Voltage	230v	230v
Weight kg	56	71
Part No.	2225455	2225460



# O Portable Engine Driven Compressor - PP9ND

This tank mounted, engine driven air compressor is ideal for mobile applications where there is no electricity supply.

- ▶ 4.0Hp Honda GC135 engine.
- Filter/regulator with gauge and twin outlets.
- ▶ 50 litre receiver.



MODEL	Displ. cfm	Engine hp	Receiver Itrs	Dimensions LxWxH (mm)	Weight kg	Part No.
1 PP9ND	9.0	4.0	50	1000x430x790	50	2090920
2 CFP9ND	9.0	4.0	2.65	520x360x440	21.0	2090900

# Portable Engine Driven Compressor - CFP9ND

Ideal for powering staple guns, nailers, riveters, sprayguns etc. This portable petrol engine driven air compressor is a real winner for building sites, plant hire & mobile repairers. This easy to carry unit is well protected by its tough steel carry frame which provides air storage.

- Powered by a 4.0Hp Honda 4 stroke engine.
- ▶ 9 cfm air displacement (maximum pressure 7bar).
- Adjustable air pressure relief valve and gauge.
- Anti-vibration rubber feet.









HONDA

A real best seller, this wrench features a 1/2" square drive, built-in 4 position power regulator and simple push-button forward/reverse.

Part No. 3110402.

See Page 34

CAT22B

🕡 1/2" Reversible Ratchet - CAT22B

1/2" square drive, reversible for added versatility.

1/2" Drive

Part No. 3110401.

See Page 29

CAT23B

See Our Full Range Of Air Tools And Spray Equipment On Pages 25-38

# **14.** AIR COMPRESSORS

# Portable Engine Driven Air Compressors











First choice for plant hire, service yards, mobile maintenance crews, farmers etc. Full protection steel frames are available fitted to these petrol driven portable machines. (see model numbers PPH).

## **TOP QUALITY FEATURES INCLUDE:**

D Genuine Honda engines. ▶ Pressure unloading genie on continuous running petrol machines. ▶ Cast iron cylinder (15's only) for longer life and greater efficiency.
 ▶ Twin cylinder pump. ▶ Fitted after-cooler above 10cfm. ▶ Slow running Compressor

above 10cfm. Slow running Compressor pumps with bladed flywheel for efficient air cooling. Fitted filter/regulator on all units in table below. Heavy duty, for years of reliable tough daily use. Fully tested in our own UK plant before despatch. Painted for long lasting protection and durability.

PPH15ND



BUILT IN OUR OWN UK PLANT



Includes Tough Protective Steel Frame



\*Great for site use, these highly efficient 'v' twin machines include fitted filter/regulator for controlled clean air and genuine Honda engines

Disp	lacemen	t Receiver	Engine	Engine/Motor	Dimensions	Net	
Model	CFM	Capacity Litres	Make	HP	(LxWxH) mm	Weight kg	Part No.
PPV11ND	10	50	Honda	4.0	1000x400x780	68	2091220
2 PPVH11ND	10	50	Honda	4.0	1100x490x807	75	2091225
PPH15ND	15	50	Honda	6.5	1000x490x807	63	2091000
PP15ND	15	50	Honda	6.5	1100x400x780	60	2090980



First choice for plant hire, construction sites, service yards, mobile maintenance crews etc.

- Genuine 6.5Hp Honda petrol engine.
- ▶ 50 litre receiver.
- Twin cylinder pump.
- 15 cfm displacement.
- Cast iron cylinder for longer life and greater efficiency.
- Fitted filter/regulator.
- Pressure unloading genie.
- Heavy duty, for years of reliable use.
- Fully painted for lasting protection and durability.







Model	Description	Dims. (LxWxH) mm	Weight	Part No.
O PP15YB	Fitted handle	1000x400x780	60kg	2091005
PPH15YB	Full frame	1100x490x807	63kg	2091010





# **BRITISH BUILT FOR PERFORMANCE** & RELIABILITY



# & 2 Electric Driven 'V' Twin Compressors

These highly efficient 'V' Twin machines feature:


Cast iron air compressor pump. Max. working pressure of 10.5 Bar (150 psi). Fitted with an automatic pressure control switch. Deach machine is built to latest European Standards specification, tested & certified. > Fitted with filter/regulator for controlled clean air.

First choice for plant hire, service yards, mobile maintenance crews, farmers etc. Full protection steel frames are available fitted to electric portable machines. (see model numbers beginning PEH).

Top quality features include: Deast iron cylinders for longer life and greater efficiency. Deast iron pump on all models on page except PE15C > Twin cylinder pumps. > Fitted after-cooler above 10cfm. > Slow running compressor pumps with bladed flywheel for efficient air cooling. Fitted filter/regulator on all units in table below. I Heavy duty, for years of reliable tough daily use. Fully tested in our own UK plant before despatch.

Fully painted for long lasting protection and durability.





Electric Driven	Electric Driven Air Compressors											
	Displacement	Receiver	Engine/Motor	Dimensions	Net	Part No.	Part No.	Part No.				
Model	cfm	Cap. Ltrs	Нр	(LxWxH) mm	Wt Kg	110v (O/L)* & (WIS)†	1PH/230v (O/L)*	1PH/230v (WIS)†				
PE15C50ND	14	50	3	940x400x760	77	2085542	2085536	2085537				
PEH15C50N	I <b>D</b> 14	50	3	1010x450x760	80	2085543	2085521	2085522				
O PE16C	14	50	3	940x400x760	76	-	2083200	-				
PEH16C50	14	50	3	1100x490x780	79	-	2085750	-				

<sup>\*</sup> Overload protection. † With wired starter PEH models include full protection steel frame.

# 16 AIR COMPRESSORS

# **Industrial Air Compressors**



TRADITIONAL STYLE AND LONG

BRITISH BUILT FOR PERFORMANCE & RELIABILITY

▶ Strong sturdy construction designed for highly reliable daily use in workshops, garages, factories & on farms. ▶ Your precise requirements suited from our huge range including electric, petrol & diesel stationary or portable machines. ▶ We fully test every compressor in our own UK manufacturing plant before despatch. ▶ 12 months' warranty with first class spares & service back-up. ▶ Reliability & durability guaranteed. ▶ Only highest quality components used in manufacture.







SE16CS100



€ SE16C200

(5) SE19200ND

Our Best Selling SE16 Is Now Built With A 100, 150 Or 200

Litre Air Receiver





2 SE15C150ND

**Vertical Space Saver Design** 



Overload protection (OL or WIS). Max working

pressure 10.5 Bar. Deliver Automatic pressure control switch Deliver Built to latest European Standards specification, tested and certified. Deliver Property Property Built to latest European Standards specification, tested and certified. Deliver Built to latest European Standards specification, tested and certified. Deliver Built to latest European Standards specification, tested and certified. Deliver Built to latest European Standards specification, tested and certified. Deliver Built to latest European Standards specification, tested and certified. Deliver Built to latest European Standards specification, tested and certified. Deliver Built to latest European Standards specification, tested and certified. Deliver Built to latest European Standards specification, tested and certified. Deliver Built to latest European Standards specification, tested and certified. Deliver Built to latest European Standards specification, tested and certified. Deliver Built to latest European Standards specification, tested and certified. Deliver Built to latest European Standards specification, tested and certified and

DIGHT KE INDUSTRIAL



VE15A150ND

				Receiver			Net	Part No.	Part No.	Part No.
		Disp.	No. of	Capacity	Motor	Dimensions	Weight	1 PH/230V	1 PH/230V	3 PH/400V
	Model	cfm	Cylinders	Litres	hp	(LxWxH) mm	kg	(O/L)**	(W/S)*	(W/S)*
-	<b>1</b> SEV11C100	9	2	100	2.0	1180x380x850	85	2081060	2091230	2091235
	2 SE15C150ND	14	2	150	3.0	1350x430x850	99	2084610	2084615	2084635
	3 SE16C150	14	2	150	3.0	1350x430x900	97.5	2081310	-	2081350
	SE16CS100	14	2	100	3.0	1180x380x880	90	2081251		
	5 SE16C200	14	2	200	3.0	1690x440x900	129	2081311		
	SE18C200ND	18	2	200	4.0	1500x480x920	124	2084645	-	2084650
	<b>6</b> SE19C200ND	18	2	200	4.0	1690x440x940	136	2084660	-	2084665

\*\* Complete with Motor overload protection. Vertical Air Compressors

\*Complete with combined pressure switch and starter.

			Receiver			Net	Part No.	Part No.	Part No.
	Disp.	No. of	Capacity	Motor	Dimensions	Weight	1 PH/230V	1 PH/230V	3 PH/400V
Model	cfm	Cylinders	Litres	hp	(LxWxH) mm	kg	(O/L)**	(W/S)*	(W/S)*
VVE11A150	9	2	150	2.0	710x500x1405	88.5	2091240		
<b>VE15A150ND</b>	14	2	150	3.0	700x760x1650	110	-	2090411	2090417
VE18A150ND	18	2	150	4.0	700x760x1650	115	2090421	-	2090431
VE25A150	23	2	150	5.5	700x760x1720	130	-	-	2090440

<sup>\*\*</sup> Complete with Motor overload protection.



ELECTRIC AIR CO	OMPRESSORS			Receiver					
Model	Displacement cfm	No. of Stages	Pump Speed rpm	Capacity Litres	Motor hp	Dimensions (LxWxH) mm	Weight kg	Part No. 1PH/230v (O/L)**	Part No. 3PH/400v (WIS)*
SE25C200	23	2	1500	200	5.5	1690x440x1020	150	-	2081380
① SE26C200	23	1	1180	200	5.5	1500x480x1000	156	-	2081610
SE29D270ND	28	2x1	1400	270	2 x 3.0	1720x550x920	163	2084701	-
SE36C270	30	2	1400	270	7.5	1670x440x1130	229	-	2084800
3 SE45C270	40	2	1300	270	10.0	1670x440x1150	234	-	2084900
SE70C300	70	2x2	1100	300	15.0	1800x800x1350	430	-	2080360
SE90C300	90	2x2	1500	300	20.0	1800x800x1350	450	-	2080400

Petrol/Diesel Air Compres	ssors							
	Displacement	Engine	Engine	Dimensions		Reciever Capacity	Weight	
Model	cfm	Make/Type	hp	(LxWxH) mm	Starter	Litres	kg	Part No.
5 SP15ND	15	Honda/Petrol	6.5	1270x460x870	Recoil Rope	150	99	2090575
SP27C150 ‡‡	25	Honda/Petrol	8.0	1350x430x950	Recoil Rope	150	119	2090735
SP27EC150 ‡‡*	25	Honda/Petrol	8.0	1350x430x950	12V Electric Start	150	119	2090737
SD25L ‡‡	25	Lombardini/Diesel	6.0	1350x430x950	Recoil Rope	150	149	2085280
SD25LE ‡‡*	25	Lombardini/Diesel	6.0	1350x430x950	12V Electric Start	150	149	2085290

<sup>\*</sup> Battery not included ‡‡ These units are for use outside EEC

# **Continuously Rated Industrial Electric Motors**

All Totally Enclosed, Fan Ventilated & **Continuously Rated** 

# These Top Quality European Motors are Ideal for Reliable Long Term Service



Our top quality range of single and 3 phase motors are ideal for reliable long term use.

Full range of single and 3 phase up to 20hp

Manufactured to the latest electrical and mechanical standards including IEC34-1, BS5000, CEN, HD231 & IEC72.

All models are totally enclosed fan ventilated cage pattern metric type, continuously rated for reliable long term service.

# **Technical Features**

- Standard Keyway shaft.
- Foot mounting (B3).
- Permanent capacitors on single phase.
- Precision balanced rotor for vibration-free operation and extra long bearing life.
- Double shielded self-lubricating radial ball bearings.
- Stator windings have Class F insulation and are impregnated with Class H resin.







# Dimensions (mm) - 1 and 3 Phase


Frame															
Size	Α	В	C	D	Ε	F	F*	* G	Н	-	L	L*	* M	N	0
63	100	80	40	11	23	155	176	124	63	120	183	185	12.5	4	4
71	112	90	45	14	30	171	192	142	71	134	215	213	16	5	5
80	125	100	50	19	40	200	222	158	80	152	240	238	21.5	6	6
90 S	140	180	56	24	50	216	216	178	90	170	255	255	27	8	7
90 L	140	125	56	24	50	216	243	178	90	170	280	282	27	8	7
100 L	160	140	63	28	68	238	268	194	100	192	305	308	31	8	7
112 M	190	140	70	28	68	267	-	220	112	220	332	-	31	8	7
132 S	216	140	89	38	80	308	-	262	132	260	382	-	41	10	8
132 M	216	178	89	38	80	308	-	262	132	260	420	-	41	10	8
1 phase machines only **															

## **Specification - 1 Phase**

		Оросии	Jacioni	1 1 1140	•	
Нр	Kw	Pole (speed)	Frame	Volts	Wt (kg)	Part No.
0.33	0.25	2 (3000)	63	230	4.6	6310203
0.33	0.25	4 (1500)	71	230	6.1	6310403
0.50	0.37	2 (3000)	71	230	6.3	6310205
0.50	0.37	4 (1500)	71	230	7.1	6310405
0.75	0.55	2 (3000)	71	230	7.2	6310208
0.75	0.55	4 (1500)	80	230	9.2	6310408
1.00	0.75	2 (3000)	80	230	8.8	6310210
1.00	0.75	4 (1500)	80	230	10.7	6310410
1.50	1.10	2 (3000)	80	230	10.3	6310214
1.50	1.10	4 (1500)	90	230	13.7	6310415
2.00	1.50	2 (3000)	80	230 *	11.9	6310225
2.00	1.50	2 (3000)	80	110	11.9	6310226
2.00	1.50	2 (3000)	90	230	14.8	6310220
2.00	1.50	4 (1500)	90	230	15.7	6310420
3.00	2.20	2 (3000)	90	230 💥	16.8	6320234
3.00	2.20	2 (3000)	90	110	16.8	6320228
3.00	2.20	2 (3000)	100	230	20.3	6310230
3.00	2.20	4 (1500)	100	230	22.6	6310430
4.00	3.00	2 (3000)	100	230 💥	22.5	6330259
With b	uilt-in Ove	erload Protection	*			

# **Specification - 3 Phase**

		- Post.		•		
Нр	Kw	Pole (speed)	Frame	Volts	Wt (kg)	Part No.
1.00	0.75	2 (3000)	80	400	8.3	6330210
1.00	0.75	4 (1500)	80	400	9.9	6330410
1.50	1.10	2 (3000)	80	400	9.6	6330215
1.50	1.10	4 (1500)	90	400	13.0	6330416
2.00	1.50	2 (3000)	80	400	10.5	6330221
2.00	1.50	4 (1500)	90	400	15.0	6330420
3.00	2.20	2 (3000)	90	400	14.2	6330230
3.00	2.20	4 (1500)	100	400	19.2	6330440
4.00	3.00	2 (3000)	90	400	16.5	6330258
4.00	3.00	4 (1500)	100	400	21.5	6330450
5.50	4.00	2 (3000)	100	400	22.2	6330255
5.50	4.00	4 (1500)	112	400	27.4	6330455
7.50	5.50	2 (3000)	112	400	28.0	6330275
7.50	5.50	4 (1500)	112	400	32.0	6330475
10.0	7.50	2 (3000)	112	400	41.0	6340212
10.0	7.50	4 (1500)	132	400	51.0	6340410
12.5	9.20	2 (3000)	132	400	47.0	6340300
12.5	9.20	4 (1500)	132	400	57.0	6340350
15.0	11.0	2 (3000)	132	400	53.0	6340216
20.0	15.0	2 (3000)	132	400	62.0	6340230



# Continuously Rated Industrial Electric Motors



This great new range of single & three phase motors are unbeatable value for money. All totally enclosed, fan ventilated & continuously rated for reliable long-term service.

▶ Full range of single & 3 phase up to 20Hp

- ▶ Foot mounting (B3) ▶ Standard Keyway shaft
- Capacitor start & run Aluminium frame & rotor
- Precision balanced rotor for vibration-free operation
- Double shielded self-lubricating radial ball bearings

Starter windings have Class F insulation & are impregnated with Class H resin

Star Delta, Direct On Line and Combined Pressure Switch/Starters Available See Page 20

# 230v Single Phase Motors

	† 2 Pole = 3000 rpm & 4 Pole = 1500 rpm					
	Size HP	Shaft Speed†	Frame Size	Shaft Dia.	Starter Rqd (Amp)	Part No.
	1/3	2 Pole	71	14mm	2-4	6430425
	1/3	4 Pole	71	14mm	2-4	6430426
	1/2	2 Pole	71	14mm	2-4	6430427
	1/2	4 Pole	71	14mm	2-4	6430428
	3/4	2 Pole	71	14mm	4-6.3	6430429
	3/4	4 Pole	80	19mm	4-6.3	6430430
	1	2 Pole	80	19mm	4-6.3	6430431
	1	4 Pole	80	19mm	4-6.3	6430432
	1.5	2 Pole	80	19mm	6.3-10	6430433
	2	2 Pole	100 L	19mm	6.3-10	6430461
	1.5	4 Pole	90 S	24mm	6.3-10	6430434
	2	2 Pole	80 S	19mm	6.3-10	6430435
	2	4 Pole	90 S	24mm	10-16	6430437
	3	2 Pole	100 S	28mm	10-16	6430438
	3	4 Pole	100 L	28mm	10-16	6430439
	2	2 Pole	90L	24mm	10-16	6430466
	4	2 Pole	100L	28mm	16-20	6430471
ı						

# 400v 3 Phase Motors

† 2 Pole	† 2 Pole = 3000 rpm & 4 Pole = 1500 rpm				
Size	Shaft	Frame	Shaft	Starter	Part
HP	Speed†	Size mm	Dia.	Rqd (Amp)	No.
1	2 Pole	80mm	19mm	2-4	6430472
1	4 Pole	80mm	19mm	2-4	6430473
1.5	2 Pole	80mm	19mm	2-4	6430474
1.5	4 Pole	90mm	24mm	2-4	6430475
2	2 Pole	80mm	19mm	2-4	6430476
2	4 Pole	90mm	24mm	4-6	6430477
3	2 Pole	90mm	24mm	4-6	6430478
3	4 Pole	100mm	28mm	4-6	6430479
4	2 Pole	90mm	24mm	6-10	6430480
4	4 Pole	100mm	28mm	6-10	6430481
5.5	2 Pole	100mm	28mm	6-10	6430482
5.5	4 Pole	112mm	28mm	6-10	6430483
7.5	2 Pole	112mm	28mm	10-16	6430484
7.5	4 Pole	112mm	28mm	10-16	6430485
10	2 Pole	112mm	28mm	Star Delta	6430486
10	4 Pole	132mm	38mm	Star Delta	6430487
12.5	2 Pole	132mm	38mm	Star Delta	6430488
12.5	4 Pole	132mm	38mm	Star Delta	6430489
15	2 Pole	132mm	38mm	Star Delta	6430490
20	2 Pole	132mm	38mm	Star Delta	6430491

## 1 - Static Phase Converters

Suitable for running 3 phase 400v electric motors from single phase 230v supply.

- 230v input point, three phase output socket.
- Ammeter for measuring incoming current from the single phase supply.
- ON/OFF switch with neon indicator that illuminates when load is connected.
- Durable steel case with powder coated finish.
- For use with drills, lathes, milling machines, circular saws.
- Variable output power, to match HP of motor to be run.



Items 1-4 Convert 230v 1ph to 400v 3ph



# Rotary Phase Converters

For motors, which are started & stopped in fairly rapid succession, where more than one motor is being run or reversing of the motor is required.

▶ Ideal for air compressors, welders, plasma cutters, garage equipment, multi-head cutting machines, presses & much more. ▶ Self-balancing output. ▶ When selecting, consider the largest motor to be run, & select a converter at least twice the size of this power.

Model	Max. Motor Hp	Fuse	Dims LxWxH	Weight	Part No.
1 PC20	2Hp	10amps	265x220x335mm	13kg	6012785
PC40	3.5Hp	13amps	365x255x385mm	19kg	6012790
3 PC60	5.5Hp	20amps	365x255x385mm	21kg	6012795
RT4	5.5Hp	25amps	355x450x440mm	70kg	6012837
RT7	10Hp	40amps	475x510x420mm	110kg	6012839
RT11	15Hp	63amps	480x500x420mm	110kg	6012841
RT15	20Hp	80amps	540x579x435mm	150kg	6012843

# **Air Compressor Components**

# 1 - 3 Air Compressor Pumps - MK/BK

Cast iron cylinders with extra deep finning, plus maximum fan cooling from the flywheel ensure low operating temperatures and drier air giving longer life and greater efficiency.

All units have two cylinders and all include inlet filter.



# Direct On Line Starters With Overload Protection

Suitable for single or 3 phase supply.
Select according to the running amperage of your electric motor.

. ,	
Amp Range	Part No.
2 - 4	6170104
4 - 6.3	6170106
6.3 - 10	6170110
10 - 16	6170116
16 - 20	6170125
20 - 25	6170128



# Combined Pressure Switch/Overload

These motor protection switches are supplied complete with thermal overload protection. This range covers motor sizes 0.5hp to 10hp.

•	•
Amp Range	Part No.
2 - 4	6170505
4 - 6	6170510
6 - 10	6170515
10 - 16	6170520





# 4 & 5 Cast Iron Pumps - CE20, CC35, CC40 & CC55

CE20

Built to the latest engineering designs these cast iron, 150psi max. working pressure compressor pumps combine reliability with outstanding performance.

AIR COMPRESSOR PUMPS								
Mo	del	Cylinders	Displacement (cfm)	Motor (hp)	After Cooler	Inter Cooler	2 Stage	Part No.
O	M3	Twin Cyl	14	3.0	✓	-	-	1390085
0	MK113	Twin Cyl	18	4.0	✓	-	-	1390090
2	BK114*	Cyl	23	5.5	✓	✓	✓	1390100
2	BK119*	Twin Cyl	30	7.5	✓	✓	✓	1390105
	BK20*	Twin Cyl	40	10.0	✓	✓	✓	1390005
3	BKV40*	V4 Cyl	70/90	15-20	✓	✓	✓	1390040
4	CE20	V Twin Cyl	9	2.0	-	-	-	1393105
6	CC35	Twin Cyl	14	3.0	✓	-	-	1393112
	CC40	Twin Cyl	18	4.0	✓	-	-	1393114
	CC55 *2 stage p	Twin Cyl	23	5.5	✓	-	-	1393115
	- stage p	ab						

# Star Delta Starters

These industrial motor protection switches are supplied complete with thermal overload protection and adjustable timer to switch between start and running modes. They are suitable for motors 10hp upwards.

•	
HP	Part No.
10	6170211
15	6170221
20	6170225

# 1 Phase Pressure Switches

For accurate automatic compressor control, these pressure switches are the simplest, most cost effective solution. Available to suit most applications. Fitted with bleed valves.



# Compressor & Airline Oil

Grade	Volume	Part No.
SAE30	1 litre	3050796
	5 litres	3050801
SAE40	1 litre	3050810
	5 litres	3050802
Airline Oil	1 litre	3050825
Compressor Oil for SHHH Air Compressors	1 litre	3050795



Design may vary.

1 PHASE PRESSURE SWITCHES					
4 Port Switch 1 Port Switch					
Model	1 Phase	1 Phase			
Max. Volts	230	230			
Max Amps	20	20			
Max Pressure PSI/Bar	175/12	175/12			
Cable Glands	✓	✓			
On-off switch	✓	✓			
Part No.	2000442	2000115			



Description	Part No.
Quick Release (Snap) Bodies	
1/4" Snap Male Body	3030210
1/4" Snap Female Body	3030205
1/2" Snap Male Body	3030325
Snap Adaptors	
3 1/4" Snap Male Adaptor	3030235
1/4" Snap Female Adaptor	3030240
Snap Hose Adaptors	
<sup>1</sup> /4" Snap Hose Adaptor	3030225
<sup>5</sup> /16" Snap Hose Adaptor	3030220
5 3/8" Snap Hose Adaptor	3030215
Hose Connectors	
6 1/4" Nut x 5/16" Tail	3030275
<sup>3</sup> /8" Nut x <sup>3</sup> /8" Tail	3030270
1/4" x 1/4" Hose Connector	3030315
<sup>1</sup> /4" x <sup>5</sup> /16" Hose Connector	3030230
√ 1/4" Nut x 1/4" Tail	3030280
Hose Joints	
1/4" Hose Joint	3030260
5/16" Hose Joint	3030255
3/8" Hose Joint	3030250
Nipples	
1/4" Nipple	3030295
3/8" Nipple	3030290
9 <sup>1</sup> /2" Nipple	3030285
Reducing Nipples	
3/8" x 1/4" Nipple	3030305
1/2" x 3/8" Nipple	3030320
Reducing Bush	
1/2" x 1/4" Reducing Bush	3030300
1/2" x 3/8" Reducing Bush	3030310
'Y' Coupler	
1 2 Way 'Y' Coupler Adaptor	3030265
, , ,	

## **Pressure Gauges** For accurate compressed air pressure measurement. 1/4" BSP Bottom Connection, 50mm dial Part No. 2000171. ▶ 1/4" BSP Centre Back Connection. 50mm dial Part No. 2000175. ▶ 1/8" BSP Centre Back

running

Part No. 2100177.

machines.

Pressure Gauges with Pressure Marking 1/4" BSP 50mm Dial

**Designed to meet European** pressure equipment

Connection. 40mm dial Part No. 2300170.

directives.

10 bar back entry Part No. 2000162.

Part No. 2000163. 8.0 bar back entry

Part No. 2000164. 7.5 bar back entry

Part No. 2000161.



## **Anti Vibration Mountings**

These fully adjustable heavy duty floor mountings are available for stationary compressors.

Set of 4, for compressors with air receiver size up to 160 litres.

Part No. 8950400.

Set of 4, for compressors with air receiver size 200-300 litres. Part No.

8950420.



**CE Safety Valves** Tough metal safety valves.

Part No. 1/4" BSP Thread (8.8 Bar) 2000191 1/4" BSP Thread (10 Bar) 2000192 3/8" BSP Thread (10 Bar) 2000195 3/8" BSP Thread (11 Bar) 2000197

# **Non-Return Valves**

Precise and reliable, for use with pressure switch control.

Item	Part No.
3/8" BSP	2002196
1/2" BSP	2002198
3/4" BSP	2002205
1" BSP	2002210



## **Hose Clips**

Quality hose clips in a range of sizes

Size	Per Pk.	Part No.
7-10mm	3	8133695
10-18mm	3	8133700
14-24mm	2	8133705
24-36mm	2	8133710
32-52mm	2	8133715
47-67mm	2	8133720
62-82mm	2	8133725
82-106mn	12	8133730



# Valves and Drain Taps (Not Illustrated)

Drain Cock	Part No.
1/8" Drain Tap	2000221
<sup>3</sup> /8" Drain Tap	2000220
Ball Valves	
1/2" Ball Valve	2000705
3/4" Ball Valve	2000710
1" Ball Valve	2000715

# 10m Air Hose (300psi) – 1/4" BSP Swivel Nut Connectors

Part No. 3125751.


Flexible rubber casing resistant to oil, abrasion and

1/4" BSP swivel nut/tail fitted on each end

Nitrile Rubber Hose With Reinforced

**Polyester Casing** 





# **Airline Accessories & Equipment**

# 6mm Recoil Hose Fitted with 1/4" BSP swivel nut connectors.

▶ High quality hose with reinforced polyester casing.

CAT58 - 25ft. (7.6M) Part No. 3110458. CAT59 - 50ft. (15M)

Part No. 3110459.

CRH9 - 9 Metres professional recoil hose. Part No. 3120100.



# 8mm (5/16" Bore)

Length	Part No.
10 Metres	3125605
15 Metres	3125610
30 Metres	3125615
50 Metres	3125620

# 10mm (3/8" Bore)

1/4" BSP nut & tail.					
Length Part No					
10 Metres	3125800				
15 Metres	3125805				
30 Metres	3125810				

3/8" BSP nut & tail. Length Part No. 10 Metres 3125815



Braided

Hose



Model		Part No.
3M -	1/4" BSP nut & tail	3125447
10M -	1/4" BSP nut & tail	3125448
30M -	No Fittings	3125451

# Whip Hose

G CAR15PC

Retractable Air Hose Reels

Hose Length

15M

9M

15M

8M

Model

CAR15PC

CAR9PC

CAR15MC

CAR8MC

Rubber hose for use between air tools and air supply, to prevent vibration damage to couplings.

660mm length (inc. fittings), 8mm ID, 15mm OD.

Connectors <sup>1</sup>/4" BSP (Female)/Snap adaptor. Part No. 3120105.



# 9 8mm Racing Air Hose (300psi) 1/4" BSP Swivel Nut Connectors

Stylish rubber air hose for use in racing/ automotive workshops.



Model	Part No.
10M Long	3125960
15M Long	3125965
30M Long	3125970

Protective Cushioned End Sleeves

# Retractable Air Hose Reels

5 & 6 CAR9PC and CAR15PC

Reinforced PVC hose in a plastic case with 1/4" BSP (Male) air inlet and 1/4" BSP (Male) outlet connections, includes mounting bracket



15M Hose

2 & 8 CAR8MC and CAR15MC

Rubber hose in a steel reel with 1/4" BSP

connections. Includes mounting bracket.

(Female) air inlet and 1/4" BSP (Male) outlet

**Hose Type** 

PVC

PVC

Rubber

Rubber

Items
5 - 8
Supplied
With
Mounting
Brackets



Weight

7kg

3.1kg

16kg

Part No.

3126000

3126005

3126100

3126105

**Reel Case** 

**Plastic** 

**Plastic** 

Steel

Steel

# 10mm (3/8" Bore) Solvent Hose

Ideal for use with paints, solvents, degreasing agents, etc. Includes <sup>3</sup>/8" BSP fittings.

**5MSHF** - 5 Metres. Part No. 3125405.

**10MSHF** -10Metres. Part No. 3125410.





Max. Pressure

300psi (20Bar)

200psi (14Bar)

300psi (20Bar)

300psi (20Bar)

Air Inlet Size

1/4"

1/4"

1/4"

1/4"

Mini Air Filter

Drain - MF2

close to the air tool or

spray-gun for maximum filtration

Unit with Auto

Mini Filter Unit with Auto Drain is a compact in-line

air filter, ideal for a range of

applications and can be sited

# 🚺 1/2" Filter Regulator - CAT41

High capacity filter/regulator unit. Complete with 1/2" x 1/2" connecting nipple, 1/2" x 1/4" reducer and bracket.



1/2" In-Line Air Filter With Auto Drain - CAT75 In-line filter with 1/2" x 1/4" BSP reducers.

4 1/2" In-Line Air Filter - CAT76 In-line air filter with 1/2" x 1/4" BSP reducers.



FR1

📵 Mini Air Regulator Unit - RC1

Ideal for ensuring the correct air pressure is applied to air tools. Pressure gauge and

1/4" BSP inlet & outlet connections



# **Filter Regulator**

1 CAT41

1/2" In-Line Air Regulator With Gauge - CAT77 Includes mounting bracket and 1/2" x 1/4" BSP reducers. Ideal for ensuring the correct air pressure is applied to air



Lubricator



Filter Regulator

Features a gauge, twin 1/4" BSP tap outlets and

3/8" BSP inlet connection.

Aluminium body with

chrome plated tube.

## 10 Filter Regulator - FR2

Features a gauge, twin 1/4" BSP tap outlets and 1/4" BSP inlet connection.

Aluminium body with chrome plated tube.

Includes wall mounting



# Tilter (Tilter) Regulators - AN1

Featuring circle-flow separator and twin 1/4" tap outlets. Includes wall mounting bracket and 1/4" BSP inlet connections.

with aluminium body and chrome plated tube. M AN1

> Includes Twin 1⁄4



# Combined Filter Regulator - CMF2/CMF3

Combined filter/regulator with pressure gauge and lubricator.

Two versions available:

CMF2 = 1/4"Part No. 3090200

tools.

CMF3 = 1/2"Part No. 3090205

3-in-1 **Filter** Regulator Lubricator



# Filter Regulator (Ideal For Professional Bodyshop Use) - AN3

Featuring a highly efficient "sintered" bronze element and circle-flow separator, twin 1/4" tap outlets and aluminium body with chrome plated tube.





		Inlet	Outlet	Max. Flow	Max. Supply	Max. Outlet	
Model	Description	BSP	BSP	Rate at 6.2 Bar	Pressure	Pressure	Part No.
<b>1</b> CAT41	Air Filter Regulator	1/2" F	1/2" F	41 cfm	8 bar	6 bar	3110441
2 CAT42	Airline Lubricator	1/2" F	1/2" F	110 cfm	8 bar	6 bar	3110442
3 CAT75	Air Filter with Auto Drain	1/2" F	1/2" F	110 cfm	8 bar	6 bar	3110775
CAT76	Air Filter	1/2" F	1/2" F	110 cfm	8 bar	6 bar	3110780
MF2	Mini Air Filter	1/4" F	1/4" F	17.66 cfm	10 bar	8.5 bar	5100810
6 RC1	Mini Air Regulator	1/4" M	1/4" M	40 cfm	10 bar	8 bar	5100812
CAT77	Air Regulator with Gauge	1/2" F	1/2" F	77 cfm	8 bar	6 bar	3110785
CMF2	Filter/Regulator/Lubricator	1/4" F	1/4" F	35 cfm	10 bar	9 bar	3090200
CMF3	Filter/Regulator/Lubricator	1/2" F	1/2" F	75 cfm	8.5 bar	9 bar	3090205
FR1	Filter Regulator	$^{3/8}''M$	2x1/4"M	40 cfm	12 bar	10 bar	5100800
U FR2	Filter Regulator	1/4" M	2x1/4"M	40 cfm	12 bar	10 bar	5100802
O AN1	Industrial Filter/Regulator	1/4" M	2 x1/4" N	60 cfm	14 bar	14 bar	5100606
♠ AN3	Bodyshop Filter/Regulator	1/2" M	2 x1/4" M	85 cfm	14 bar	14 bar	5100706



# **Pressurised Sandblaster** - CPSB100

▶ Heavy duty steel construction ▶ Removes surface rust, paint, dirt/grease etc. Pressurised design gives greater power than its siphon fed equivalent Facility to control the sand & the outlet air fl 32 litre (7.04 gallon) tank capacity Working pressure 4.4 - 8.6Bar (65 - 125psi)

Safety shut off valve Inc. 4 ceramic nozzles (2,

2.5, 3, 3.5mm), ressure gauge, hose, ood & funnel Flow rate req. 6-19cfm Dims



Replacement Nozzles (Pack of 4)

Part No. 7640132



Compact and lightweight durable moulded casing with convenient carry handle and integral hose storage. 14 litre tank capacity. Long 4.5m (14ft 7") grit hose. Includes sandblasting gun and delivery hose.



Siphon Feed Sandblaster CSB10

Quickly removes paint, surface rust, dirt/ grease, burrs etc. Suitable for use with aluminium oxide (up to 60 grit), garnet powder & glass beads.

16.8 litre tank capacity ≥ 3Hp ≥ 1/4" BSP

Departing pressure 101psi (7 Bar) Flow rate reg. 10-16cfm 10ft suction hose Inc. sandblasting gun, delivery hose, 4 ceramic nozzles (sizes 4-7) & safety hood Dims (LxWxH) 378x279x744mm

Part No.7640117



16.8 Litre Tank Capacity

Ideal for rust

grit

removal and stone

cleaning, suitable for use

Includes 1 litre container,

with aluminium oxide

1/4" BSP Air inlet and

Operating pressure 80-100psi. Min air

requirement 8cfm.

Part No. 5091101.

8mm hose tail.

CSB10



Great for removing paint, rust, dirt/grease, burrs from metals, brick and stone. Suitable for use with

aluminium oxide (up to 60 grit), garnet powder & glass beads 34 litre tank capacity.

Flow rate req. 10-16cfm ) 8ft grit hose Inc. sandblasting gun, delivery hose, 4 ceramic nozzles (sizes 4-7mm) & safety hood/mask > Working pressure 6-8Bar (87-116psi)

Part No. 7640120

**Extra Large** 34 Litre Capacity

> Replacement Nozzles (Pack of 4) Part No. 7640122



CSB34

# Sandblast Kit with Pickup Hose

For precision blasting, with 3m air hose to reach inaccessible areas and pick up tube to collect grit from a bucket or bag.

- Suitable for use with aluminium oxide grit.
- Includes extra nozzles and 1/4" BSP fitting.
- Operating pressure 80-100psi. Min air requirement 8cfm.

Part No. 5091103.





SB5

👩 SB4

# Portable Sandblaster Hopper Kit - CPSB1





CPSB1

Replacement Nozzles (Pack of 5)

Part No. 7640127

14 Litre Tank

Capacity

Long 4.5m (14ft 7")

**Grit Hose** 

# 🔽 Spotblast Kit - SB5

SB3

Gritblasting Gun - SB3

Perfect for rust spot removal on vehicle bodywork.

Collection bag enables blasting media to be recycled. Contains an assortment of blasting nozzles - for flat surfaces, corners and panel edges. Duitable for use with aluminium oxide grit. DWith 1/4" BSP male snap adaptor. Deperating pressure 80-100psi. Min air requirement 8cfm. Part No. 5091105.


# 🔞 - 🕧 Aluminium Oxide Powder Suitable for use with our range of sand

blast cabinets, spotblast and grit guns. Blasts deep to remove rust, paint corrosion and limescale. Also suitable for removal of paint and grafitti, etching and surface preparation. Can be used on all metals, brick, concrete and masonry.

Grit Weight (Kg) Part No. **3** 60 22 3052070 **9** 80 3052075 22 **120** 22 3052080 **1** 60-80 3052100 7.5 **2** 80-120 7.5 3052105 **1** 60-80 20 3052110







# 🔼 Sprav Gun - PSC

This versatile non-bleed, external mix syphon spray gun suits the smaller air compressor and has separate controls for material flow and fan shape. 750ml cup.

▶ 1.2mm nozzle. ▶ Air requirement 3cfm. ▶ Sprays most conventional paints. ▶ 1/4" BSP fitting. Duse air compressor 1hp or larger.



Particularly suited for operation with smaller compressors without an air receiver. The JS Spray Gun is a constant bleed, pressure fed gun complete with round and fan internal

1 litre cup. 1.3mm nozzle. 1/4" BSP fitting. Use air compressor approx 0.75 Hp.



# 6 Air Texture Gun - CTG8


Ideal for the hire trade and professional builders/decorators, this high capacity unit is designed for large surface coverage and will handle most textured wall and ceiling

Tough 7.95 litre (1.75 gal) (plastic) composition hopper with support handle. 4 nozzles and 5 spray pattern areas give a total of 20 different combinations. > 45° offset connector for ceiling work. ▶ Requires 6-25cfm depending on aircap and nozzle configuration.



# **Quality Spraying Equipment**





# Pressurised Paint Feed **Container - CPP2**

For large area paint spraying in spraybooths, garages & workshops.

comes complete with pressure gauge, regulator safety valve, 1.8M air & fluid hoses with BSP fittings & carry hook. The following Spray Guns are compatible with this Paint Pressure Containers; PRO12C/14C/18C, SP14C/18C, PSC,

AP15HVLP CPP2. 2 litres.

Part No.

2 Litre 3110232



Spray Gun Not Included

# 🗐 Pro Airbrush Kit - CAB2P

Features double action trigger for accurate air/paint control & precision machined nozzle.

Spray pattern adjustable from 1/32" to 11/2".

2 jars, special lightweight hose.

1/4" BSP adaptor and useful chromed paint cup.

Part No. 3110315.

AP15



# DIY Airbrush Kit - CAB1H Ideal for model makers, artists, etc.

- Spray pattern adjustable from 1/8" to 2".
- Includes 2 jars, special lightweight air hose.
- 1/4" BSP adaptor and propellant regulator. Part No. 3110310.



# 🚺 Pressure Valve & Gauge - PV&G1

Fits neatly onto the base of the gun handle to allow quick & accurate checking & adjustment of the working pressure of air tools. For air outlets & inlets of 1/4" BSP. Gauge reads in

psi & bar.


Part No. 3090105.



Top quality paint tanks for large surface area spraying, Ideal for vehicle body repairs. garages, workshops and production lines. Fitted with a non corrosive inner paint pot that can easily be lifted out for cleaning, (CPP5 aluminium paint pot, CPP40 stainless steel paint pot), air safety valve, carry handle and pressure regulator. CPP40 is mounted on castors for easy manoeuvrability. Paint stirrer included.









- Screw top.
- Moisture free propellant 500ml. Part No. 3051105.





Model	① CPP5	CPP40
Capacity Itr	4.2	43.4
Part No.	3110234	3110237



Rubber Air Hose See Page 22

# **DIY Workshop Air Tools**

This great value range is ideal for the DIY mechanic.

# 1/2" Reversible Ratchet Wrench - CAT108

A versatile, reversible tool ideal for automotive and workshop use.

- Includes a rubberised comfort grip
- Maximum speed 160rpm
- Max torque 50ft/lb
- Operating pressure 90psi (6.2 Bar)
- Average air consumption 4cfm

Part No. 3120110



1 CAT108

1 - 6

# 2 3/8" Reversible Ratchet Wrench - CAT109

A versatile, reversible tool ideal for automotive and workshop use.

- Includes a rubberised comfort grip
- Maximum speed 160rpm
- Max torque 50ft/lb
- Operating pressure 90psi (6.2 Bar)
- Average air consumption 4cfm

Part No. 3120116



Ideal For Automotive And Workshop Use



# 3 1/2" Impact Wrench - CAT110

1/2" Drive

Suitable for garage, tyre shop and workshop applications. **Built-in 4 position power** regulator and simple push button . forward/reverse mechanism.

- Includes a rubberised comfort grip
- Maximum speed 7000rpm 1/2" Drive
- Max torque 230ft/lb
- Operating pressure 90psi (6.2 Bar)
- Average air consumption 8cfm

Part No. 3120120



**Built-In 4 Position Power Regulator** 



Ideal for sanding auto body panels, wood, metal, fibreglass sheet and plastic to give a perfect finish.

Maximum speed 8000rpm

Operating pressure 90psi (6.2 Bar)

Average air consumption 6cfm Pad size 90 x 165mm

Part No. 3120126



on all items except CAT 111







Great for grinding and polishing metal components. The die grinder includes a rubberised comfort grip and the kit comes supplied with 10 grinding stones, 2 wrenches, collet, 1 snap connector and all stored in a handy carry case.

- Maximum speed 22,000rpm
- Operating pressure 90psi (6.2 Bar)
- Average air consumption 4cfn

Part No.

3120132





# 6 3" Cut-Off Tool - CAT 113

A versatile tool especially designed for cutting auto body panels, light sheet metal plus exhaust, muffler or radiator hose clamps and nuts & bolts. Fitted with a metal safety guard and a throttle safety device to prevent accidental operation.

- Includes a rubberised comfort grip
- Maximum speed 18,000rpm
- Operating pressure 90psi (6.2 Bar)
- Cut-off disc size 1.6 x 76mm dia.

Part No. 3120135



		Required	Average	Approx	Max.	Air Inlet	
Model	Description	Air Pressure	Air Consumption	Max. Torque	Speed	Size	Part No
① CAT108	1/2" Reversible Ratchet	90psi (6.2 Bar)	4cfm	50ft/lb	160rpm	1/4" BSP	3120110
② CAT109	3/8" Reversible Ratchet	90psi (6.2 Bar)	4cfm	50ft/lb	160rpm	1/4" BSP	3120116
3 CAT110	<sup>1</sup> / <sub>2</sub> " Impact Wrench	90psi (6.2 Bar)	8cfm	230ft/lb	7000rpm	1/4" BSP	3120120
CAT111	Orbital Sander	90psi (6.2 Bar)	6cfm	-	8000rpm	1/4" BSP	3120126
5 CAT112	1pc Die Grinder Kit	90psi (6.2 Bar)	4cfm		22000rpm	1/ <sub>4</sub> " BSP	3120132
6 CAT113	3" Cut-Off Tool	90psi (6.2 Bar)	4cfm	-	18000rpm	1/4" BSP	3120135

**AIRTOOLS** 



For 25 Years this Top Quality range has proven highly reliable for tough daily use in garages and professional workshops.



# 4 32 Piece 3/8" & 1/2" Metric/AF Impact Socket Set - CIS9/32

1/4" Drive

2 1/4" Reversible Ratchet - CAT55

Compact 1/4" square drive ratchet, reversible for added

Heavy duty. Flatdrive for extra grip. 32 piece: 3/8" square drive sockets 8, 9, 10, 11, 12, 14, 15, 16, 17mm.

- 1/2" square drive sockets 17, 19, 22, 30mm & 1/2", 9/16", 11/<sub>16</sub>", 13/<sub>16</sub>", 1", 1<sup>1</sup>/<sub>8</sub>". Deep sockets 13, 15, 17, 18, 19, 21, 22, 24, 27, 30mm.
- Extension bars 3/8" x 3" & 1/2" x 3" adaptor 1/2" F, 3/8" M.
- Supplied in robust moulded case.
- Weight: 6kg.

versatility.

Part No. 3110500.

CAT55

Part No. 1800305.



3/8" Reversible Ratchet - CAT21B

3/8" square drive, reversible for added versatility.



1/2" Reversible Ratchet - CAT22B

1/2" square drive, reversible for added versatility.





**Top Quality** Chrome Vanadium Impact Sockets For Air Tool Use. See Page 39 For Full Range

# 6 14 Piece 1/2" Impact Wrench & 3/8" Ratchet Set - CAT232

Two of the most popular air tools in one complete set. Includes 10 chrome vanadium impact sockets: 10, 12, 13, 14, 16, 17, 19, 21, 22, 24mm, plus  $\frac{1}{2}$ " (F) &  $\frac{3}{8}$ " (M) adaptor.



	Model	Nominal Air Consumption	Max. Speed	Max. Torque	Weight kg	Part No.	
1	CAT221B	4 cfm	160 rpm	60ft/lb	3.0	3110424	
2	CAT55	3 cfm	250 rpm	30ft/lb	1	3110500	
3	CAT21B	4 cfm	150 rpm	50ft/lb	1.0	3110400	
	CAT22B	4 cfm	160 rpm	60ft/lb	1.2	3110401	
6	CAT232	4 cfm	150 rpm	Wrench 230ft/lb	5.2	3110432	
		4 cfm	150 rpm	Ratchet 50ft/lb	(Set)		



(5) CAT232



Includes 10 Sockets

Required Air Pressure Max 90PSI (6.2 Bar), Air Inlet (All Tools) 1/4" BSP, Min Hose Size 8mm Bore

# **Professional Air Tools**

For 25 Years this Top Quality range has proven highly reliable for tough daily use in garages and professional workshops.

# PROFESSIONAL AIR TOOLS WITH HIGHLY POLISHED FINISH & COMFORTABLE RUBBER GRIP

# **COMFORT**RUBBER GRIP



\*CAT92 & CAT96 Requires 10mm bore hose

Model	Description	Reversible	Nominal Air Consumption	Max. Speed	Max. Torque	Weight kg	Part No.
① CAT90	<sup>3</sup> /8" Square Drive Reversible Ratchet	<b>V</b>	4 cfm	150 rpm	50ft/lb	1.0	3110846
2 CAT91	<sup>1</sup> /2" Square Drive Reversible Ratchet	<b>V</b>	4 cfm	160 rpm	60ft/lb	1.2	3110847
3 CAT92*	<sup>1</sup> /2" Square Drive Impact Wrench	<b>V</b>	4 cfm	-	230ft/lb	2.4	3110848
CAT96*	<sup>1</sup> /2" Square Drive Impact Wrench Kit	<b>V</b>	4 cfm	-	230ft/lb	4.0	3110852
CAT94	<sup>3</sup> /8" (10mm) Air Drill	-	4 cfm	2200 rpm	-	1.0	3110850
© CAT100	<sup>3</sup> /8" (10mm) Reversible Air Drill	<b>V</b>	4 cfm	1800 rpm	-	1.0	3110856
N.B: Maxim	um required air pressure - 6.2bar (90psi)						

3/8" Reversible
Air Drill
10mm Chuck
Planetary Gear
System Giving
Extended Life &
Low Maintenance





All Inlets 1/4"		Maximum	Nominal Air	Max.	Weight	
Model	Description	Req. Air Pressure	Consumption	Rate/Speed	kg	Part No.
① CAT93	6" Dual Action Sander, supplied with comfort grip	6.2 bar	6 cfm	8,500 rpm	1.9	3110849
CAT95	Long Stroke Air Hammer complete with 6 pc. chisel set	6.2 bar	4 cfm	3,000 blows/min	2.5	3110851
3 CAT97	High Speed Sabre Saw with 3 blades	6.2 bar	5 cfm	10,000 strokes/min	0.5	3110853
	Pack of 3 replacement blades (for CAT97)					3110429
CAT98	14 piece Die Grinder Set (in Kit Box)	6.2 bar	8 cfm	22,000 rpm	0.5	3110854
© CAT99	3" Air Cut-off Tool with disc	6.2 bar	4 cfm	21,000 rpm	0.9	3110855
	Pack of 5 replacement cutting discs (for CAT99)					3110731
<b>6</b> CAT 106	Air Metal Shear	6.2 bar	3 cfm	2,500 strokes/min	1.19	3110862

# **Professional Air Tools**

For 25 Years this Top Quality range has proven highly reliable for tough daily use in garages and professional workshops.

Air Nail Gun Kit

Rec. air pressure 4.1-6.9

Bar. Fires 18 gauge (F type)

CNG1-C

CSN-1C

G CSG1-C

Item 6

Supplied In

A Moulded

**Carry Case** 

With Oil, 4

Hex Kevs and

A Roll Of Nails

6 CON15

- CNG1-C

nails(15-50mm). 100

magazine capacity. Inc. 2 Hex keys,

lubricant & case.

Part No. 3110390.



Compact & robust design, ideal for working in limited space. Rec. air pressure 4.9-6.0 Bar. Fires 14 gauge nails (30-120mm). Inc. 2 Hex keys, **lubricant & protective** leather cover.

Part No. 3110395.

## 100 Shots **Per Minute**



OPN1

- CSG3K-C Rec. air pressure 4.1 6.9 Bar. Fires 20 gauge (type 45) staples (10-25mm). 100 magazine capacity Inc. safety goggles, 2 Hex keys, lubricant, 600x10mm staples, 400x25mm staples & case

Air Staple Gun Kit

Part No. 3110380. CSG3K-C

# **For Comfort**

Shank length Part No. Replacement 8mm 1800400 Staples for CSG1C 1800402 10mm **TYPE 71** 12mm 1800403 (Pack of 5000) Part No. Replacement Shank length Staples for CSG3KC 10mm 1800405 16mm 1800407 **4J SERIES** 1800411 22mm (Pack of 5000) Shank length Part No Replacement Staples for CSN1-C 16mm 1800429 19mm 1800431 **TYPE 90** 1800435 25mm (Pack of 5000) 1800436 32mm 1800437 40mm

Replacement	Shank length	Part No
Nails for	20mm	1800415
CSN1-C and CNG-	.1C 30mm	1800417
18 GAUGE	32mm	1800419
(Pack of 5000)	35mm	1800421
	40mm	1800423
	45mm	1800425
	50mm	1800427

Replacement	Description	Part No.
Nails for CFN34	2.87 x 50mm	1800444
(Pack of	2.87 x 65mm	1800445
200 Nails)	3.05 x 75mm	1800446
	3.33 x 90mm	1800447
CFN21	2.87 x 50mm	1800440
(Pack of	2.87 x 63mm	1800441
210 Nails)	3.05 x 75mm	1800442
	3.33 x 90mm	1800443

# 34 Degree Clipped Head Air Framing Nailer - CFN34

Heavy duty for tough professional use. For roofing, timber frames, internal partition wall etc. Ideal for toe-nailing boards together. Inc. safety yoke, oil, 4 x Hex Keys (3-6mm) & case. Nail Length 50-90mm. ▶ Nail Dia. Range 2.87-3.33mm. > 80 Magazine Capacity. Rec. air pressure 5.5-7.5 Bar.

Part No. 3110397.

Weight: 4kg

💶 2 in 1 Combi Nailer Kit -CSN-1C

Nailing and stapling functions. ▶ Inc. safety goggles, 500 staples, 1000 nails, 2 Hex keys, lubricant & case. Fires 18 gauge (type 90) staples, (16-40mm), 18 gauge (F type) nails, (15-50mm). ▶ 100 magazine capacity. Rec. air pressure 4.1-6.0 Bar. Part No. 3110385.

# 🗐 Air Stapler Kit - CSG1-C

Ideal for packaging, carpet laying, upholstery etc.

Rec. air pressure 4.1-6.0 Bar. 180 magazine capacity. Fires 22 gauge (type 71) staples (4-16mm).

Inc. 2 Hex keys, lubricant & case. Part No. 3110375.

Items (2) - (8) Come Complete With **Carry Case** 

# 6 15° Coil Nailer - CON15

A powerful, heavy duty Coil Nailer. Ideal for trade use for numerous applications including siding, sheathing, roofing, decking & fencing. Magazine capacity up to 300 pieces. Accepts nail lengths of 45-70mm. ▶ Accepts nail diameters of 2.3-2.9mm.

Departing air pressure range 70-100psi.

Weight: 4Kg

Part No. 3110295

# 21 Degree Round Head Framing Nailer Kit - CFN21.


▶ Heavy duty, for tough professional use. ▶ Ideal for roofing, for nailing joists, noggins and engineered lumber with 21 degree nail head. Inc. safety yoke, oil, 4 x Hex Keys (3-6mm) & case. Nail Length 50-90mm.

Nail Dia. Range 2.87-3.33mm. ▶ 60 Magazine Capacity.

Rec. air pressure 5.5-7.5 Bar.

Weight: 3.8kg. Part No. 3110396





	3		
Part No	Length	Shank	Pack Qty
1800462	45mm	2.3mm	300 (on Roll)
1800464	50mm	2.5mm	300 (on Roll)
1800466	70mm	2.87mm	250 (on Roll)

Replacement Ring Shank Nails for CON15

•	-		
Part No	Length	Shank	Pack Oty
1800467	45mm	2.3mm	300 (on Roll)
1800468	45mm	2.5mm	300 (on Roll)
1800469	70mm	2.87mm	250 (on Roll)









2 in 1 Needle Scaler

& Hammer

For 25 Years this Top Quality range has proven highly reliable for tough daily use in garages and professional workshops.



Needle Scaler & Hammer Kit - CAT84 2 in 1 Pistol grip needle scaler, 3 hammer chisels & chisel retaining spring.

Length of piston stroke 40mm. Part No. 3110820



CAT84 Length of piston stroke 40mm

**Tools Included** 

# 3 1/2" (13mm) Reversible Air Drill - CAT60

Comes with heavy duty, 1/2" (13mm) chuck. Handle adjustable through 360°, planetary gear system.



4 1/4" BSP Mini Oiler CAT74

Ideal in-line oiler. Helps to prolong air tool life. Fits between air tool and airline.

Part No. 3110770.

6 3/8" (10mm) Reversible Air Drill - CAT87

3/8" (10mm) chuck. Planetary gear system.

Part No. 3110835.



# 6 Long Stroke Air Hammer Kit - CAT29B

Powerful, rapid percussion for general purpose breaking, separating and cutting of most materials.

Includes a set of 6 chisels. Built in air regulator. Heavy duty chisel

retaining spring.

Part No. 3110408.



7/3/8" (10mm) Angle Air Drill - CAT61

**CAT61** 

For drilling in awkward and inaccessible areas, 10mm chuck. Part No. 3110461.



For Air Hoses See Page 22

🚯 Needle Scaler - CAT51 For fast, effective rust and scale removal.

Length of piston stroke 27mm.

Part No. 3110565.



(E) CAT51 Replacement Needle set for CAT51.

Part No. 3110566.

# **Professional Air Tools**

For 25 Years this Top Quality range has proven highly reliable for tough daily use in garages and professional workshops.



23/8" Impact Wrench - CAT78 Compact and lightweight allows easy access to confined spaces in engine bays and for transmission work.

3/8" square drive. Part No.

3110790.

CAT78

3/8" Butterfly Wrench - CAT64 Compact and lightweight, allows one handed control of forward/reverse.

▶ 3/8" square drive. Part No. 3110720.



# 4 1/2" Heavy Duty Impact Wrench - CAT81



5 1/2" Heavy Duty Industrial Impact Wrench' - CAT79

CAT79 1/2" square drive ideal for automotive and industrial use.

- ▶ 5 speed power regulator
- Twin hammer mechanism for more power and extended life under heavy continuous use.
- Max 300ft lbs torque Part No. 3110795.

6 13 Piece 1/2" Impact Wrench & Socket Set - CAT231B

Includes 10 chrome vanadium impact sockets: 9, 10, 11, 13, 14, 17, 19, 22, 24, & 27mm, plus 5" extension bar.

Part No. 3110425





**Includes Case** 

🕡 3/4" Heavy Duty Impact Wrench - CAT48

Heavy duty wrench for garage and workshop use. (7) CAT48 ▶ 3/4" square drive.

Push button forward/reverse.

Max 500ft lbs torque Part No. 3110680.

Nominal Air Max. Weight Model Consumption Part No. Torque kg **O** CAT23B 4 cfm 230ft/lb 2.4 3110402 **2** CAT78 4 cfm 60lb/ft 1.3 3110790 3 CAT64 2.5 cfm 75lb/ft 0.9 3110720 CAT81 4.2 cfm 280ft/lb 2.7 3110805 ■ CAT79 5 cfm 300ft/lb 2.7 3110795 6 CAT231B 4 cfm 230ft/lb 3110425 4 **CAT48** 7.5 cfm 500ft/lb 5 3110680

42 Piece Professional Air Tool Set - CAT88

Includes: CAT23B - 1/2" Impact Wrench, CAT24B - 6" Dual Action Sander CAT29B - Air Hammer, CAT87 - 3/8" Reversible Drill, CAT36B - 1/4" Die Grinder. Accessories include:

4 air chisels, 10 die grinding stones, 1/4" and 1/8" collets, 10 impact sockets, 9, 10, 11, 13, 14, 17, 19, 22, 14, 27mm, extension bar, reducer, 4 screwdriver bits, sanding pad, oil bottle, spanners & blow moulded case.

Part No. 3110840.




5 Most Popular Air Tools In One Superb Set

Note: Required Air Pressure Max 90PSI (6.2 Bar), Air Inlet All Tools 3/4" BSP. Min Hose Bore Size 8mm (10mm Hose For CAT79, 81, 23B, 231B).

See Page

28 & Stop Press



For 25 Years this Top Quality range has proven highly reliable for tough daily use in garages and professional workshops.



Push button forward and reverse function. 380 ft/lb (516 Nm) of maximum torque and 7000rpm maximum speed. Average air consumption: 4.2cfm. Air Connector type: 1/4" BSP. Dimensions: (LxWxH)



### (3) Industrial 1/2" Air Impact Wrench - CAT103

Ideal for use in automotive/ industrial workshops.

1/2" Square drive wrench with 2" Anvil and 5 speed settings. > 400 ft/lb (542 Nm) maximum torque and 8000rpm maximum speed. > 5 speed power regulator.

Average air consumption: 4cfm.

Air connector type: 1/4" BSP.

Dimensions: (LxWxH) 245x73x186mm.

Weight: 2.78kg.

Part No. 3110859.

Long 2" Anvil

For More Air Impact Wrenches See Page 30 & 34

4 9 Piece 3/4" Metric Impact Socket Set - CIS19/9M

Heavy duty. 9 piece: 26, 27, 29, 30, 32, 35, 36, 38mm. Supplied in tough steel case. Weight: 4kg. Part No. 1800320.



CAT74

11 Piece 1/2" Metric Impact Socket Set - CAT37B

> 1/2" Square drive: 10, 11, 12, 13, 14, 17, 19, 21, 22, 24mm sockets. Supplied in steel tray. Weight: 1.3kg.



⑥ 1/4" BSP Mini Oiler - CAT74

Ideal in-line oiler. Helps to prolong air tool life. Fits between air tool and airline.

Part No. 3110770.



Suitable for garage, tyre shop and workshop applications. Built-in 4 position power regulator and simple push button forward/reverse mechanism. Comes with 10 chrome vanadium impact sockets, a 125mm (5") extension bar and in-line lubricator.

Maximum speed 7000rpm Max torque 230ft/lb Doperating pressure 90psi (6.2 Bar) Average air consumption 8cfm Chrome vanadium impact sockets: 1x9mm, 1x10mm, 1x11mm, 1x13mm,

1x14mm, 1x17mm, 1x19mm, 1x22mm, 1x24, 1x27mm

Part No. 3110873.



(2) CAT117

Includes 10 Chrome Vanadium Impact Sockets 9-27mm



For fast, accurate sheet metal cutting. Cutting capacity 1.2mm in mild steel/aluminium.

4 way adjustable punch head (left/right/ forward & reverse). Min. cutting radius 25mm. Part No. 3110463.

7) CAT63



Ideal for crimping and hole punching.

Crimping capacity 1.6mm steel, 2mm aluminium. Hole size  $\sqrt[3]{16}$ " (4.8mm). Part No. 3110462. CAT62

### **Professional Air Tools**

For 25 Years this Top Quality range has proven highly reliable for tough daily use in garages and professional workshops.



### 13Pc Angle Die Grinder Set - CAT65

Allows access to difficult to reach grinding areas. Includes 10 aluminium oxide grinding stones and  $^{1}/^{8}$  and  $^{1}/^{4}$  collets. Supplied in tough moulded carry case.



	Model	Nominal Air Consumption	Max. Speed	Weight kg	Part No.
0	CAT73	4 cfm	-	2.5	3110765
<b>2</b>	CPR2	4 cfm	-	1.8	3110285
3	CAT66	4 cfm	21,000	0.9	3110730
4	CAT65	8 cfm	18,000	0.5	3110725
<b>5</b>	CAT36B	8 cfm	22,000	0.5	3110436
6	CAT89	8 cfm	22,000	0.9	3110845






# 25 Piece Sanding Drum Set (With Storage Case) - CAT38 Ideal for use with CAT36B, CAT89 & CAT65 and electric drills. Contains:

Five popular sized drums, 1/2" - 2" and four metal abrasive sleeves for each size. Up to 1" suitable for Air Die Grinder. Larger sizes can be used in electric drills with lower rpm.

**DIY Kit** 

Part No. 3110438.



See Our Full Range Of Air Compressors For All Applications From DIY To Automotive/ Industrial On Pages 8-17

Clarke



For 25 Years this Top Quality range has proven highly reliable for tough daily use in garages and professional workshops.



Trigger operation.


Accepts Standard 215x50mm

Part No. 3120106.

distortion. Cutting capacity 1.6mm (16 gauge) in mild steel.



NB: Nominal Air Consumption figures are for guidance only and are quoted on the basis of average usage patterns. Allowance should be made for more intensive applications.




Note: Required Air Pressure Max 90PSI (6.2 Bar), Air Inlet (All Tools) 1/4" BSP, Min Hose Size 8mm.

### **Professional Air Tools**

For 25 Years this Top Quality range has proven highly reliable for tough daily use in garages and professional workshops.







# 3 41/2" High Speed Sander - CAT25B

Ideal for preparation work. Supplied with 100mm, 115mm & 127mm fibre backing pads. Accepts common sanding discs with 22mm bore.

Part No. 3110404.



### Orbital Sander - CAT34B

Pad size 90x165mm, auto throttle release. Built in speed regulator.





### High Speed Belt Sander - CAT40B

Adjustable sanding arm allows access in awkward places. Supplied with 80 & 100 grit belts for metal working. Belt size 10x330mm.

Part No. 3110440.





### For Replacement Belts See Table below

O CAT24B	6 cfm	8000 rpm	1.0	
		0000 ipiii	1.9	3110403
2 CAT80	6 cfm	10000 rpm	1.6	3110800
3 CAT25B	6 cfm	18000 rpm	1.5	3110404
CAT34B	6 cfm	8000 rpm	2.0	3110434
5 CAT40B	8 cfm	8000 rpm	0.6	3110440
CAT45B Pack of 4	belts $1/2$ "x12" for	CAT40B (10mmx330mm)		3110445
CAT57 Pack of 4	belts 2x80 grit, 2x1	00 grit for CAT40B (10m	mx330mm)	3110507
⑤ CAT49	8 cfm	2500 strokes/min	2.8	3110535
CAT70	12 cfm	1500 m/min	1.2	3110750
Replacement belt	60 grit (pack of 5)	for CAT70		3110751
Replacement belt	80 grit (pack of 5)	for CAT70		3110752

### Carried Bed Sander - CAT49

Reciprocating (non orbital) action for straight line flatting over large areas. Smooth twin piston action. Pad size



### 🕡 Heavy Duty Belt Sander - CAT70

Adjustable handle allows access in awkward places. Supplied with 80 & 100 grit belts for metal working. Belt size 20x520mm. Part No. 3110750.



CAT70

For Replacement **Belts See Table** 

### **AIRTOOLS**

**Professional Air Tools** For 25 Years this Top Quality range has proven highly reliable for tough daily use in garages and professional workshops.

> All Of These Socket Sets Feature Top Quality Chrome Vanadium Impact Sockets For Air Tool Use

### 13 Piece 3/8" Metric/AF (Deep) Impact Socket Set - CIS9/13

Heavy duty. 13 piece: 8, 10, 11, 13, 14, 16, 17, 19mm & 3/8", 1/2", 9/16", 11/16".

- Supplied in tough steel case.
- Weight: 1.8kg.

Part No. 1800300.





1/2" Square drive: 10, 11, 12, 13, 14, 17, 19, 21, 22, 24mm sockets.

Supplied in steel tray. Weight: 1.3kg. Part No. 3110437.



3 17 Piece 1/2" Metric/AF (Deep) Impact Socket Set - CIS12/17

Heavy duty. 17 piece: 10, 11, 12, 13, 14, 17, 19, 21, 22, 24, 27mm & 1/2", 9/16", 5/8", 11/16", 13/16". Dupplied in tough steel case.

Weight: 2kg. Part No. 1800310.



🛂 32 Piece 3/8" & 1/2" Metric/AF Impact Socket Set - CIS9/32

Heavy duty. Flatdrive for extra grip. 32 piece: 3/8" square drive sockets 8, 9, 10, 11, 12, 14, 15, 16, 17mm.

1/2" square drive sockets 17, 19, 22, 30mm & 1/2", 9/16", 11/16", 13/16", 1", 11/8". Deep sockets 13, 15, 17, 18, 19, 21, 22, 24, 27, 30mm. ▶ Extension bars 3/8" x 3" & 1/2" x 3" adaptor 1/2" F, 3/8" M. Dupplied in robust moulded case.

Weight: 6kg. Part No. 1800305.

All Of These Socket Sets Feature Top Quality Chrome Vanadium Impact Sockets For Air Tool Use



(5) 36 Piece 1/2" & 3/8" Square Drive Impact/AF Metric Socket Set - CIS12/35

3/8" Square Drive 6 Point Sockets: 3/8", 1/2", 9/16", 11/16".

AF and 8, 9, 10, 11, 12, 13, 14, 17mm. 1/2" Square Drive 6 Point Sockets: 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 1" AF and 9, 10, 11, 12,

13, 14, 15, 17, 18, 21, 22, 24, 27, 30mm. Extension Bars: 3/8" x 75mm, 1/2" x 75mm.

Drive Adaptor: 1/2" F x 3/8" M.

Part No. 1800340.





🕡 8 Piece 1/2" Square Drive

Socket Set - CIS12/7MD

Universal Joint (Deep) Impact

Heavy duty. 9 piece: 26, 27, 29, 30, 32, 35, 36, 38mm.

- ▶ Supplied in tough steel case.
- Weight: 4kg.

Part No. 1800320.




9 7 Piece Impact TRX-Star 1/2" Square Drive Set - CIS12/6S

For use with all square drive wrenches. 1/2" Square Drive TRX-STAR Wrench x 78mm.

- T30, T40, T45, T50, T55, T60, T70.
- Supplied in tough storage case.

Part No. 1800360.





(5) CIS19/9M

Part No. 1800350.





### 6 Piece 1/2" Square Drive Impact Hex Key Set - CIS12/6H

Hardened, tempered and chemically blackened for durability.

Adjustable for use with all wrenches and ratchets. ▶ 1/2" Square Drive Hex Wrench x 60mm. ▶ 8, 10, 12, 14, 17, 19mm. ▶ Supplied in tough storage case.

CIS12/6H

Part No. 1800355.





Air Impact Wrenches See Pages 30, 33 & 34



### **Portable Petrol Driven Generators**

### 1 & 2 Inverter Generators

These top quality low noise, portable generators are highly effcient, have 4 stroke engine and feature:

Inverter technology for clean, stable power. Eco throttle for greater fuel efficency and low noise Low oil and overload shutdown.

(I) IG1000

# Clarke IG1000 1kw Inverter Generator Lightweight with low noise output ideal for camping, carayanning, boats, markets etc. and can

camping, caravanning, boats, markets etc. and can also be used on sensitive equipment such as computers and laptops.

▶ Eco Throttle system to keep fuel consumption and

noise to a minimum 12v battery charging facility (12v DC@ 5amps) Includes standard 13amp, 230v socket 1000W max, 900W continuous output Low oil shutdown Overload shutdown

Weight 15Kg

Dimensions 460x250x420mm Part No. 8877050.

Stroke



13 Include Standard

Quiet Running (Only 64 DBA At 1/4 Load At 7 Metres)

Engine
Not To Be Confused
With Noisier Oil
Burning 2 Stroke Units

Clarke Manager Control of the Contro

G720 -

Stroke

**Engine** 

Not To Be Confused With Noisier Oil Burning 2 Stroke Units

See Stop Press

Items 1 & 2 - Inverter Technology Produces Pure, Stable Power - Essential For Computers & Sensitive Equipment



2 IG2200

Quiet Running (Only 60.5 DBA At 3/4 Load At 7M) Stroke Engine
Not To Be Confused

Not To Be Confused With Noisier Oil Burning 2 Stroke Units

### 2 IG2200 2.2kw Inverter Generator

With a maximum output of 2.2kw and continuous output of 2.0kw this generator is suitable for trade and leisure use. It is ideal for powering computers & sensitive equipment. This model includes:

Two 13amp, 230v sockets. ▶ 12v battery charging facility (12v DC @ 8.3amps) ▶ Dimensions: 542x288x486mm

Part No. 8877055

Quiet Running (58 DBA at 7M)

**3 G950 900W Portable Generator** 

This highly portable generator can be used to provide a reliable source of power in the home, for stalls, caravanning, camping, boating etc.

▶ 900w maximum power output ▶ 12v battery charging facility (12v DC @ 5amps) ▶ Air cooled 4 stroke engine ▶ Running hours @ <sup>3</sup>/<sub>4</sub> load: 8.5h ▶ Low oil alert and overload shutdown ▶ 230v AC (13amp) socket ▶ Recoil start ▶ Dimensions 476x324x418mm.

Part No. 8010105

Model No.	Max Output Watts	Continuous Output Watts	Voltage AC	Output DC	13A 230v Sockets	Fuel Tank Capacity Litres	Running Time On Full Tank @ <sup>3/</sup> 4 load	Noise DBA at 7M	Weight kg	Part No.
1 IG1000	1000	900	230v	12v – 5A	1	2.7	6 hours	64	15	8877050
2 IG2200	2200	2000	230v	12v-8.3A	2	7	7 hours	60.5	26.6	8877055
3 G950	900	900	230v	12v-5A	1	7	8.5 hours	58	28	8010105

### 1 - 5 Petrol Generators

This superb range of petrol powered generators offers exceptional value for money and suits a wide variety of applications from domestic to trade, caterers, stall holders, local authorities and emergency services.

Features include: full protective steel frames, easy-start 4 stroke engines with oil alert, manufactured to meet the latest EU noise directives.

FG2000 & FG3000 Include Domestic Type Sockets (13A, 230v)

### 🚺 FG2000 (2.4KVA)

Supplied with large pneumatic tyred wheels for easy mobility.

Handles fold for storage







(2) FG3000 (2.8KVA)

Large 15 litre fuel tank provides up to 11 hours running at 3/4 load ▶ Full protective steel frame ▶ 12v DC output for battery charging



7 FG3000

**2.8KVA** 

2800 WATTS 6.5HP ENGINE 2x230v, 13amp SOCKETS
EXTRA LONG RUN TANK

FG3050 (3KVA)

Big 25 litre fuel tank provides up to 13 hours running at 3/4 load 2 x 16amp CEE sockets (1 x 230v, 1 x 115v) 1 x 32amp CEE socket (115v) Ideal for powering lighting,refrigeration units etc. at business & leisure events



3KVA

**8HP ENGINE** x230v & 2x115v SOCKETS **EXTRA LONG RUN TANK** 

4.5KVA) ELECTRIC START 4.5KVA

High

**Output For** 

Trade And

Emergency

Use

Electric start

(inc. battery

& leads) for

1 x 16amp

(1 x 230v, 1 x 115v)

Fold down handles & pneumatic

tyred wheels for easy mobility



4500 WATTS **11HP ENGINE** 1x230v & 2x115v SOCKETS EXTRA LONG RUN TANK **(5)** FG5100ES (5.5KVA)

**5.5KVA** 

High Output For Trade And Emergency Use

<u>4</u>0&5 Supplied With Handles & Wheels For Easy Movement **Around Site** 

> Electric (inc.battery & leads) for added convenience

Fold down handles & pneumatic tyred wheels for easy mobility ▶ Tough protective steel frame

1 x 16amp CEE socket (115v)

2 x 32amp CEE sockets (1 x 230v, 1 x 115v)

FG5100ES **5500 WATTS** 

13HP ENGINE 1x230v & 2x115v SOCKETS **LONG RUN TANK** 

Max. Voltage Engine Start **Fuel Tank** Fuel Db(A) 13A 16A 32A Dims. Weight Part Running Method HP Capacity Cons. ltr/hr 230v 230v 110v 230v 110v LxWxH Output AC Hours @ at 7M (kg) No. 3/4 Load **KVA** @3600rpm Model (Ltrs) @75% Sockets Sockets **Sockets** (mm) Recoil FG2000 2.4 230 6.5 4.5 4.5 0.8 65 575x435x420 38 8857725 FG3000 2.8 230 Recoil 6.5 11 15 1.4 69 592x498x432 45 8857700 FG3050 3 115/230 Recoil 8 13 25 1.9 69 680x510x540 8857705 FG4050ES 4.5 115/230 Electric 11 10 25 2.4 72 1100x630x645 8857715 **FG5100ES** 5.5 115/230 Electric 13 9 25 2.7 74 1100x630x645 8857720

# POWERED BY HONDA

### 1 - 6 Portable Generators (With Genuine Honda Engines)

Designed & Super efficient generators to provide you with electrical power wherever you need it. Deal for builders, contractors, mobile caterers, stall holders & persons involved in outdoor events for business, sport or leisure. Dean also be used to provide emergency power during mains supply failure. Designed & manufactured to meet the latest EU Noise Directive requirements. Designed & manufactured to meet with output via approved round pin sockets.









Jerry Cans See Page 218









Trolley Kit
For use with CP5050/
LR/ESLR, CP6050/
LR/ESLR generators.
Part No. 8130360



Model	Max. Output	Voltage AC	Engine hp	Start Method	Fuel Tank Capacity	Running Hours@	Fuel Cons.	Db(A)	16		Socket 32A	Dims. LxWxH	Weight	Part No.
Honda Petrol	KVA				(ltr)	3/4 Load	(ltr/hr)	7M	230v	115v	115V	mm	kg	
① CP2850	2.7	230/115	5.5	Recoil	3.6	3.9	0.92	70	1	1	-	610x420x410	34	8857600
2 CP2850LR	2.7	230/115	5.5	Recoil	11.0	11.9	0.9	70	1	1	-	610x420x540	35	8857605
CYB2850	2.7	230/115	5.5	Recoil	3.6	3.9	0.92	70	1	1	-	610x420x410	34	8857610
CP3550	3.4	230/115	6.5	Recoil	3.6	3.2	1.1	71	1	1	-	610x420x410	36	8857615
CP3550LR	3.4	230/115	6.5	Recoil	11.0	9.7	1.13	71	1	1	-	610x420x540	37	8857620
3 CYB3550	3.4	230/115	6.5	Recoil	3.6	3.2	1.1	71	1	1	-	610x420x410	36	8857625
CP5050	5.0	230/115	9	Recoil	6.0	3.7	1.63	71	2	2	1	690x480x540	59	8857630
6 CP5050LR	5.0	230/115	9	Recoil	15.5	9.5	1.63	71	2	2	1	710x510x600	64	8857635
CP5050ESLR	5.0	230/115	9	Electric	15.5	9.5	1.63	71	2	2	1	710x510x600	69	8857640
CP6050	6.0	230/115	11	Recoil	6.5	3.7	1.75	72	2	2	1	690x480x540	68	8857645
CP6050LR	6.0	230/115	11	Recoil	15.5	8.8	1.76	72	2	2	1	710x510x600	73	8857650
G CP6550ESLR	6.5	230/115	13	Electric	15.5	7.2	2.16	71	2	2	1	710x510x600	87	8857655

### Stationary Diesel Generator

Ideal for home, commercial and industrial use for providing mains or standby emergency power, this heavy duty top quality generator features:

Deliater diesel 4 stroke air cooled engine. Deliavy duty, brushless, self regulating alternator (1500 RPM, 50HZ, 0.8 Power Factor). Deliamented on heavy gauge channel iron base frame. Delia 12 volt electric key switch start. Deliamented control panels include: - 1 ammeter per phase - Voltmeter and selector switch - Instrument protection fuses - Overload circuit breaker.

Standard accessories included: - Engine mounted fuel tank - Exhaust silencer

Lister Engine Generators

Model KVA Volts Phase Part No.

1 TX3/ES3 17.25 400 3 8030432



BRITISH MADE GENERATORS FOR PERFORMANCE, EFFICIENCY & LONG TERM RELIABILITY







### Industrial Diesel Generators

Our Diesel Generators are built to industrial standard using genuine Yanmar air cooled diesel engines and include technologically advanced, maintenance free Markon NAC brushless alternators.

### Features include:

- Direct Injection Yanmar diesel engine
- ▶ High efficiency exhaust silencer
- Industrial duty two wheeled trolley frame
- Dual voltage output
- Overload protection

Low Noise Sound Deadening Enclosure

TX3/ES3



# 3 & Alternators (Outputs From 2.2-6.5KVA)

These alternators (50Hz) include keyway shaft for pulley drive. Ideal for OEM and a wide variety of industrial and agricultural uses, these alternators are designed to operate at the speeds shown in the table.



Dual Voltage 240/110 On 2.2, 3.5, & 6 KVA 2 Pole Units

3000RPM (2	3000RPM (2 Pole)										
KVA	Phase	Part No.									
3 2.2KVA	1ph	8233005									
3.5KVA	1ph	8233010									
6.0KVA	3ph	8233020									
6.5KVA	1ph	8233015									

Yanmar Dies	el - Acou	stic Enclo	sure											
Model	Max.	Voltage	Engine	Start	<b>Fuel Tank</b>	Running	Fuel	Db(A)	16	6A	32A	Dims LxWxH	Weight	Part No.
	Output	AC	Нр	Method	Cap. Litres	Hrs@Load	Consumption	@7M	230v	115v	230v 115v	mm	kg	
	KVA								Soc	kets	Sockets			
CD4050	4.0	230/115	7	Recoil	3.5	3.4	1.02 ltr/hr	74	2	2		940x640x700	89	8857660
② CD5950E	<b>S</b> 6.0	230/115	10	Electric	24	17.1	1.4 ltr/hr	71	2	2	- 1	1300x740x780	174	8857665

### **Extension Cables & Adaptor Plugs**

### 🚺 - 🔼 110v Industrial **Duty Cable Reels**

These 110v cable reels are ideal for trade/site use.

- Highly portable lightweight stands for tough daily use.
- ▶ Simple pull out unwinding and easy wind up action.
- Supplied with BS EN60309 IP44 sockets. With arctic grade 1.5mm<sup>2</sup> extension cable and fitted BS4343 plug.





and 4 BS EN60309 sockets.







Ideal for garage, workshop and industrial use, these lightweight cable reels are robust enough to withstand tough daily use. All of these cable reels are protected by a thermal cut-out.

- ▶ Tough tubular steel stand.
- All units include 2 sockets and plug.

Model	Reel	Ca	ble	Volts	Part No.
		Length	Dia		
CCR250M	Metal	50M	1.25mm <sup>2</sup>	230	6155153
⑤ CCR227	Plastic	25M	1.00mm <sup>2</sup>	230	6155190
<b>⑥</b> CCR226	Plastic	25M	2.50mm <sup>2</sup>	230	6155185



**Cut-Out For Safety** 





C4WJB

❿

Heavy Duty 2.5mm<sup>2</sup> Cable





Alla Olt	, 030		
	Nominal		Part
Description	rating (amp)	Volts	No.
2 Way Adaptor Plug	16	110	6160500
32 Way Adaptor Plug	16	230	6160505
3 Way Adaptor Plug	16	230	6160555
103 Way Adaptor Plug	16	110	6160550
<b>⚠</b> Adaptor	16-13 socket	230	6160600

### **12** Generator Plugs (110v/220v) to BS4343

Polycarbonate with round brass pins. (IP44).

110v/32A. Part No. 6160114. 110v/16A. Part No. 6160112. 230v/32A. Part No. 6160113. 230v/16A. Part No. 6160111.



1



### **Electrical Surge And** Spike Protection On C24SP



### 4 In Line Trailing Socket - C24

Tough, 4-way trailing socket for the home, garage, office or workshop. Neon 'mains present' indication. Keyhole slots for wall or bench mounting. Approved to BS1363/A. With 2 metre lead and fitted 13A fused mains plug. Part No. 3220835.

### 🔱 4 In Line Trailing Socket With Surge Protection - C24SP

Robust 4-way mains filtering trailing socket with electrical surge and spike protection, suitable for use with many electrical and electronic appliances, including personal computers, hi-fi's, TV's, VCR's and games consoles. Neon 'mains present' indication. Keyhole slots for wall or bench mounting. Approved to BS1363/A. With 2 metre lead and fitted 13A fused mains plug. Part No. 3220840.

### 14 Metre 110v Extension Cable **C14EC**

Complete with 16A BS EN60309 plug and trailing socket. Part No. 3220825.

# 1 Way Trailing Extension Lead - EL14 230v

▶ IEC terminated. ▶ 14 metre/1.5mm², 230v Cable. 13amp plug & BS EN60309 16amp trailing socket. Ideal for connecting appliances with a generator type plug to mains supply. Max capacity 13amp, 3120w. Part No. 3220845.



1 28w Work Lamp - CTL28

Extra bright 28w energy saving fluorescent work lamp. Great for use in workshops, garages, lofts etc.The lamp is energy efficient, and includes an integeral power socket.

Robust build Supplied with a folding carry handle and screw holes for fixing to workbenches, walls etc

Part No. 4002905

Supplied With Integral **Power Socket** 



3 x 24w Work Lamp - CTL24/3

Extra bright energy saving fluorescent tube work lamp. Great for use in workshops, garages, lofts etc. Includes 2 integral power sockets.



▶ Robust build ▶ Supplied with a folding carry handle and screw holes for fixing to workbenches, walls etc

Part No. 4002910

Supplied With Two Integral Power Sockets



### 19 Bulb Led Headlight -CTH4AAA

This ultra bright multi-bulb headlight is fitted with powerful LEDs.

- ▶ 19 long-life high intensity LEDs
- ▶ 4 operation modes ▶ Adjustable head strap Tilting headlight
- ▶ Water resistant (non-submersible)
- ▶ Requires 3 x AAA batteries (not included) Part No. 4003165

10 Million Candle Power Extra High Power Rechargeable Spotlight - RWL10

Provides excellent illumination in either of its modes; full (100w) or half (55w). Includes a small 8w 270° rotating fluorescent

work light and a 12v DC socket which allows the user to power other 12v products.

Robust, heavy duty rubberised

casing Powered by 12v 7Ah sealed battery Rechargeable by 230v mains

adaptor or 12v in-car charging cable (included) • Battery charging indicator

Comes with integral stand and carry strap

Part No. 4002822





**LED Baseball Cap** See Page 226





### 2 LED Rechargeable Work Light - RWL 55

Can be used as a work light, warning lamp and torch. Ideal for DIY use in garages, workshops, lofts etc. Comes with a 360° swivel hook and a magnet on the reverse for hands-free applications. Supplied with 3 x rechargeable Ni-MH 'AA' batteries, mains & 12v in-car chargers and mains charger base.

3 Modes: Inspection lamp (white): 33 LEDs Flashing (red): 22 LEDs, Torch (white): 3 LEDs

Up to 20 hours working time

Part No. 4002900















Ideal for tough daily use. Includes 5 metre cable & fitted 13 amp plug.

Uses bayonet cap bulb (not supplied) with glass protector. Practical hanging hook.

▶ Tough, protective casing. ▶ Can use up to 100 watt bulb. CIL240

230v - Part No. 3220820

110v - Part No. 3220815



### Krypton Headlight CTH-3AAA-LED

Multi bulb headlamp with:

6x long life LEDs for general lighting. 1 x centre focusing long beam krypton bulb. Tilting function. Adjustable headstrap. Requires 3x AAA batteries (not included).

Part No. 4003160.

CTH-3AAA-LED

🕡 Underbonnet Worklight - CHU100 Easy mounting 30w 900mm fluorescent lamp via rubber covered clamps > Adjustable brackets allow lamp to fit to most bonnets (1150 -1800mm wide) Detachable lamp can be used separately or hung vertically via a 360°

(included) Part No. 3220823.

swivel hook





3 Million Candle **Power Rechargeable** Spotlight - RSL3


Ideal for camping, caravanning, breakdowns etc plus trade and home use. Provides 25w illumination. It also includes a 7w fluorescent work light and an LED night light.

Powered by 6v 4Ah sealed battery Rechargeable by 230v mains adaptor or 12v in-car charging cable (included) Dattery charge level indicators Inc. stand and two position handle Part No. 5460480



# 46 ELECTRICAL EQUIPMENT

### Halogen Flood Lights (110v & 230v) & Transformers



16A

12

255x166x220

3220760

### 16 - 19 Heavy Duty Portable Transformers

Built for tough daily site use, these transformers convert 230v AC into 110v AC. Duilt-in overload protection. Complies to BS3535 (EN 60742). Arctic grade mains lead. Centre tapped to earth.

		Power Tool	Socket	Outlets	Weight	Dims.	
	Model	Rating	No.	Type	kg	LxWxH mm	Part No.
ı	1 CTR3000/2	* 3300VA	2	16A	17	236x195x265	3220785
	① CTR4000/2	4000VA	2	16A	20	184x184x261	3220900
ı	① CTR5000/3	5000VA	2/1	16A/32A	32	311x311x275	3220906
l	① CTR6300/3	6300VA	2/1	16A/32A	40	355x311x275	3220910



(T) CTR750/1

British Built For Performance & Reliability (Items 10-14, 16-19)

TR1000/1

(15) CTR3000/2

All Of These Transformers Include 2M Mains Lead & Plug

CTR1500/2 1500VA

# 1260w Twin Head Halogen Floodlights - CHL1260T/CHL1260C

• Great for lighting building sites, auto repairs, gardens and for emergency use

Can be used indoors and out Floodlight has twin lamps with individual on/off switches and either 230w, 400w or 630w output per lamp Mounted on an adjustable tilt/swivel bracket

▶ Fitted with metal grills to protect clear glass lenses and bulbs from damage ▶ CHL1260T includes an adjustable height tripod from 0.9m up to 2m (max lamp height 2.03 Metres)

**CHL1260T** (with tripod) Part No 5460595 **CHL1260C** Part No 5460600







10 & 2

630w Per Head

> Extends to 2M High



Watts	Part No.
400	5460605
230	5460610

**RT15** 

20Hp



Suitable for running 3 phase 400v electric motors from single phase 230v supply.

- 230v input point, three phase output socket.
- Ammeter for measuring incoming current from the single phase supply. NON/OFF switch with neon indicator that illuminates when load is connected.
- Durable steel case with powder coated finish.
- For use with drills, lathes, milling machines, circular saws. Variable output power, to match HP of motor to be run.







		p			
Model	Max. motor Hp	Fuse	Dims LxWxH	Weight	Part No.
3 PC20	2Hp	10amps	265x220x335mm	13kg	6012785
O PC40	3.5Hp	13amps	365x255x385mm	19kg	6012790
5 PC60	5.5Hp	20amps	365x255x385mm	21kg	6012795
Model	Max. motor Hp	Fuse	Dims LxWxH	Weight	Part No.
6 RT4	5.5Hp	25amps	355x450x440mm	70kg	6012837
RT7	10Hp	40amps	475x510x420mm	110kg	6012839
RT11	15Hp	63amps	480x500x420mm	110kg	6012841

80amps

540x579x435mm

150kg

6012843

### **6** Rotary Phase Converters

For motors, which are started & stopped in fairly rapid succession, where more than one motor is being run or reversing of the motor is required.

- Ideal for air compressors, welders, plasma cutters, garage equipment, multi-head cutting machines, presses & much more. Self-balancing output.
- When selecting, consider the largest motor to be run, & select a converter at least twice the size of this power.



### **Digital & Analogue Multimeters**



Automatic over range and polarity indicators. ▶ 10 Amp facility. ▶ Diode and transistor test (hFe). Doverload protection. \ Low battery indicator. Measures: AC/DC Volts, DC Current,

32 Position Digital Multimeter

Resistance.

Supplied in a tough protective case, this unit includes:

Automatic over range and polarity indication.

10A). Measures: AC/DC Volts, AC/DC Current, Resistance. Easy To Read




A superb example of diagnostic equipment, ideal for professional, DIY & hobby use. Measures:

DC volts (0-500v). DC current (0-10amps). Resistance (0-20MΩ). Dwell angles (3-12 cylinders). DRPM (0-10,000rpm on 3-12 cylinders). Also includes:  $\triangleright$  10M $\Omega$  input impedance for measuring sensitive on-board computer controlled components. Auto polarity indicator diode test and audible continuity test.



# - CDM20 CDM20



### Digital Clamp Meter - CDM85

**Displays** 

Ideal for the automotive electrician & test engineers.

Non contact readings via clamp

Audible continuity

Data hold function

▶ Safe one-handed

current measurement LCD display with

backlight Dverload protection Pair of test leads, 3 x 3V batteries & full instructions

included. Weight 0.17Kg

Dimensions 151x65x34mm

1 CDM10

### Digital Multimeter - CDM15

The CDM15 is a handy pocket-sized meter combining full professional features with neat, compact styling. Unit includes:

Protective wallet. Deverload protection. Integral test probes clip neatly to body for tidy storage.

Diode and audible continuity test. Both units measure:

Current, Resistance. Features Checklist See Table On **Opposite Page** 

CDM85

AC/DC Volts, DC

### 6 Analogue Multimeter - CDM3

Compact pocket meter for DIY and general use.

16 position rotary function and range selector. Integral battery tester (range 1.5V to 9V). Diverload protection. Measures: AC/DC Volts, DC Current, Resistance.





Model	No. of positions	Ranges AC Volts (No	Ranges DC o.) Volts (No.)	Ranges AC Current (No.)	Ranges DC Current (No.)	Ranges Resistance	Diode test (No.)	Transistor HFE test	Full Overload protection	Part number
① CDM10	19	100mV to 600Vrms (2	100µV 2) to 600V (5)	-	100nA to 10A	100m $\Omega$ to 2M $\Omega$ (5)	1mA Fixed Current	10mA Base Current	<b>V</b>	4500005
2 CDM20	32	100µV to 700Vrms (5	100µV to 5) 1000V (5)	10nA to 10A	10nA to 10A (7)	$0.1\Omega$ to $20M\Omega$ (6)	1mA Fixed Current	10mA Base Current	V	4500007
3 CA500	23	-	0.0V to 500V	-	0 to 10A (3)	$0.1\Omega$ to $20M\Omega$ (2)	-	-	<b>V</b>	4500480
CDM85	8	1V to 600V (1	1V to 600V (1)	1A to 400A (3)	N/A	$1\Omega$ to $200$ K $\Omega$ (2)	-	-	<b>V</b>	4500095
5 CDM15	6	1mV to 500Vrms (2	1mV 2) to 500V (4)	-	0.1mA to 200mA (1)	$1\Omega$ to $2M\Omega$ (4)	0.8mA Fixed	-	<b>V</b>	4500040
6 CDM3	16	0.4V to 500V (4	0.05V to 4) 500V (5)	-	10μA to 250mA (3)	$0.1\Omega$ to $200 \mathrm{K}\Omega$ (2)	-	-	<b>V</b>	4500030

### This Superb Range Combines High-Tech Performance With Unbeatable Value For Money

### Top of the range, these professional multimeters (CDM 35, 45) feature:

▶ Protective shock resistant holster complete with probe holders and variable height stand. ▶ Diode, transistor and audible continuity test. ▶ Automatic over range and polarity indication. ▶ Full overload protection on all ranges (except 20A on CDM 35 and CDM 45).

## Digital MultimeterCDM35

Ideal for general electrical and workshop testing. Measures: AC/DC Volts, AC/DC Current, Resistance.

> Shock Resistant Holster



CDM45

Includes °C Temperature Probe

Large Easy To Read Displays

3 Digital Multimeter With Temperature Probe - CDM45

Ideal for electrical/mechanical engineers. Measures: AC/DC Volts, AC/DC current, Resistance.

▶ Temperature (-50° to +700°C) with 'K' type probe supplied (0° to 40°C without probe). Capacitance.

CVC1

Me	odel	No. of	Ranges AC	Ranges DC	Ranges AC	Ranges DC	Ranges	Diode test		Full Overload	
0	CDM35	positions 30	<b>Volts</b> ( <b>No.</b> ) 100μν to	<b>Volts (No.)</b> 100μν	Current (No.) 0.1µA to	Current (No.) 0.1µA to	Resistance (No.) $0.1\Omega$ to	1mA Fixed	<b>HFE test</b> 10µA Base	protection <a href="mailto:vertical"> V </a>	<b>Part No.</b> 4500055
			700vrms (5)	to 1000v (5)	10A (6)	10A (6)	$20M\Omega$ (6)	Current	Current		
8	CDM45	30	100μν to 700vrms (5)	100μν to 1000ν (5)	10μA to 10A (8)	1μA to 10A (4)	$0.1\Omega$ to $200\text{M}\Omega$ (7)	1mA Fixed Current	100mA Base Current	<b>V</b>	4500065

(T) CA600

CDM80

### Pen Probe Digital Multimeter - CDM80

Delimine design, ideal for testing in confined or hard to reach places Delta Auto-ranging multimeter with rotary dial Delta Large, high contrast LCD display Delta and value hold Part No. 4500085

### **10** Battery & Alternator Tester - CA600

Ideal for use on cars and vans A quick, easy method for checking the condition of your car battery and alternator charging voltage LEDs light up showing the condition of the battery and state of the alternator Tests 12v batteries Part No. 4500090

### **1** Voltage Tester - CVC1

Voltage tester, used to measure the voltage of live wires safely. ▶ Tests AC & DC supplies. ▶ 1.0M flexible lead. ▶ 12v – 600v range. Part No. 4500130

**Features Checklist** CDM10 CDM20 **3** CA500 CDM85 CDM15 CDM3 CDM35 CDM45 CDM80 4500005 4500007 4500480 4500095 4500040 4500030 4500055 4500065 4500085 Audible continuity Data hold function Auto off Transistor test HFE Diode test Over range indicator Polarity indicator Low battery indicator Battery included Wallet/case Protective holster Overload protection



Tests

AC & DC Supplies



### **Multi-Function Detectors**, **Digital Tachometers & Infrared Thermometers**

### 1 - 3 Super Detectors - CDM65, CDM70 & CDM75

These detectors accurately locate hidden metal pipes, live wires, and studding. All have auto indicators. The CDM70 additionally has digital display, self-calibration and auto switch off. The CDM75 6-in-1 Super Detector & Estimator can also be used to measure and calculate distance, area and volume (with imperial & metric readouts).

Auto indicator. Battery included.






- ✓ Wood ✓ Distance
- ✓ Metal ✓ Area ✓ Cables ✓ Volume
- **CDM75**



**Displays Imperial And Metric Measurements**  Calculates Distance, Area & Volume





### Infrared Thermometer - IRT-1

Allows temperature measurement without physical contact, which can aid fault diagnosis.

- Compact thermometer with wide temperature range (-20°C to 520°C)
- Displays in Celsius or Fahrenheit
- Built-in laser pointer.
- Display hold feature. Part No. 4501010.

Large, Easy To



**Power Off** 

Microwave Leakage **Detector - CDM60** 

DIY microwave leakage detector, used to detect microwave radiation.

- Compact and easy to use.
- No batteries required.
- Dims (LxWxH) 175x71x28mm.
- Weight 44g.

Great For Checking The Output Of Microwave Ovens, Mobile Phones Etc.





# 6 & 7 Digital Multimeters & Tachometers

Non-contact meter analyses light reflected off a moving object into the meter and converts it into an RPM value.

Reflector strips are provided for measurement.

Part No. 4501110.

Part No. 4501115. **Supplied With** Protective Case

Digital Contact Tachometer - CT2

shaft for surface speed measurement.

Supplied with a cone tip and rubber wheel for

**1 CT2 Digital** CT1 Digital Laser Model contact Tachometer **Tachometer** Measurement 5-19,999rpm Range 0.05-1,999.9m/min 5-99,999rpm 0.2-6560ft/min Resolution 0.1rpm - 1.000rpm 0.1rpm - 1.000rpm 1rpm ≥ 1.000rpm 1rpm ≥ 1.000rpm Accuracy  $\pm (0.05\% + 1 \text{ digit})$  $\pm (0.05\% + 1 \text{ digit})$ Dimensions LxWxH 170x72x37mm 190x72x37mm Sampling time 1sec (over 6rpm) 1sec (over 6rpm) 4501110 Part No. 4501115



Offering full professional specification including on/off (non-live) torch, these best selling top quality MIGs are unbeatable value for money. First choice for auto body work, they are ideal for hobby, professional & light industrial users alike.

Professional type torch with full on/off control of power, wire feed and gas.

steel or aluminium). Wheels and handle for easy transportation on MIG 135TE, 150TE, 151TE. Powerful wire drive motor. Metal roller wire feed with infinitely variable wire speed control. Provision to carry spare gas bottle (Red machines carry 1 bottle only).

■ 150TE fitted with rotary power selector, for easy operation. ■ Thermal overload protection. ■ 230V/1 Phase operation.

Complete with CO2 gas bottle, welding torch, gas regulator, steel welding wire, earth clamp, face mask (with BS 679 glass) and full operating instructions.

All 'TE' Models Are Fan Cooled For Longer Use At Full Output And Include Wheels And Handle



Model         (Turbo)         (Turbo)           Max amperage         90         100         150         100         130           Amperage at 60% duty         30         40         75         40         57	
	(Turbo)
Amperago at 60% duty 30 40 75 40 57	150
Amperage at 00 /0 duty 50 40 /5 40 5/	75
Min amperage 24 30 30 30 30	30
<b>Open circuit voltage</b> 18-26 21-28 18-28 21-28 18-26	18-28
Input voltage 230 230 230 230 230	230
Max metal thickness (mild steel) 3-4mm 4-5mm 6mm 4-5mm 5mm	6mm
<b>Welding wire sizes mm</b> 0.6-0.8 0.6-0.8 0.6-0.8 0.6-0.8 0.6-0.8	0.6-0.8
Power settings 4 5 6 4 4	6
Dimensions (LxWxH) mm 430x250x370 430x250x370 700x320x580 500x280x420 680x350x470	680x350x470
Weight kg 24 25 32 25 29	30
Part No. 6010296 6010909 6010141 6015110 6015135	6015151

Wheels And Handle On MIG135TE, MIG151TE & MIG150TE

### 110E, 135TE Turbo, 151TE Turbo

In addition to the features described above, these superb machines also include;

- ▶ Hinged side door for fast easy access when changing wire. ▶ Extra tough protective edging front and rear. ▶ Rotary power selector switch on 151TE Turbo makes power selection even easier.
- Wheels & handle on 135TE & 151TE.

# Dual Purpose Gas/No-Gas MIG Welders For DIY & Professional Use

### 🕦 - 🙆 90EN, 100EN, 105EN & 151EN

These dual purpose machines offer the advantages of standard MIG welding but without the need for gas bottles. Each of them can easily be converted for use with gas. A special flux-cored wire which produces its own gas shroud as it burns, allows these machines to weld steel without a bottled gas supply, simplifying their use. Outdoor use is easier since there is less chance of blowing away the shrouding effect of the gas.

### These machines include:

- Turbo fan cooling for greater efficiency (Except 90EN).
- Multiple power settings for accurate welding power control.
- ▶ 90EN, 100EN, 105EN, 110EN, 130EN have 4 power settings. 151EN has 5 settings and 160EN has 6 settings. ▶ Flux cored steel welding wire. ▶ Torch with full on/off control. ▶ All units convertible for use with gas for welding aluminium, mild and stainless steel. ▶ All units complete with earth clamp, face mask (with BS679 glass) and full instructions. Note: For welding with gas, simply purchase the appropriate wire, tips, gas and regulator (See Page 54).



Wiodei	O SUEIN O	IUUEIN (TUIDO)	IUSEIN (TUIDO)	Odini) Mai Gi	UIUEIN (IUIDO)	U 130EN (IUIDO)	U IOUEIN (IUIDO)
Max Amperage	90	100	100	150	100	130	150
Amperage 60% Duty	30	55	48	62	55	57	75
Min Amperage	24	30	30	30	30	30	30
Open Circuit Voltage	18-26	18-27	21-29	21-32	18-27	18-26	18-28
Input Voltage/Phase	230-1	230-1	230-1	230-1	230-1	230-1	230-1
Wire Sizes mm*	0.6/0.9	0.6/0.9	0.6/0.9	0.6/0.9	0.6/0.9	0.6/0.9	0.6/0.9
MaxThickness (Mild Steel mm)	3-4	4-5	4-5	5	4-5	4-5	5-6
Power Settings	4	4	4	5	4	4	6
Dimensions (LxWxH) mm	430x250x370	430x250x370	130x250x370	430x250x370	500x280x420	500x330x435	500x330x435
Weight kg	23	28	22	25	25	25	28
Part No.	6010107	6010103	6014010	6014100	6014500	6014530	6014560

<sup>\*</sup> Flux cored wire (for gasless welding) is 0.9mm, gas welding wire is 0.6 & 0.8mm diameter



											1	
Turbo MIG Welders		Amperage		Open circuit	Input	Wire sizes	Max metal thickness	Wire spool capacity	Wire feed speed max	Dimensions (LxWxH)	Weight	Part
Model	Max	60%	Min	voltage	voltage	mm	(mild steel) mm	(kg)	(m/min)	mm	kg	No.
MIG160TM	150	75	30	18-28	230	0.6/0.8	4-5	Mini-5	17	750x370x550	36.0	6015530
MIG165TEM	155	80	30	18-29	230	0.6/0.8	4-5	Mini-5	17	750x370x550	36.0	6015535
3 MIG175TECM	170	85	30	23-42	230	0.6/0.8	5-6	Mini-5	17	750x370x550	37.0	6015540
MIG195TEC	185	103	30	23-42	230	0.6/0.8	6-7	5-15	18	750x390x720	47.0	6015500
■ MIG205TE	185	80	30	23-30	230	0.6/0.8	6-7	5-15	18	750x390x720	47.0	6015205
MIG230TEC	210	103	30	23-46	230	0.6/0.8	7-8	5-15	18	750x390x720	47.0	6015505
MIG220TE	200	123	30	21-43	230	0.6/1.0*	10-11	5-15	19	830x500x740	71.0	6015220
	250	150	30	21-48	230	0.6/1.0*	10-11	5-15	22	830x500x740	79.0	6015510
MIG270TE	260	170	30	17-38	400	0.6/1.0*	10-11	5-15	22	830x500x740	79.0	6015240
MIG455TE	400	310	30	18-46	400	0.6/1.2*	20	5-15	22	1120x555x1340	143.5	6010415

**9** 

Bodyshop & Workshop Welding

<sup>\*</sup> With optional wire feed roller.

### **MIG Welding Accessories**



A full range of gases, wires, tips, shrouds etc. is available both in standard and display packaging.

### Accessories For DIY/Semi Professional MIG Welders

Additional of Billy Collin 1 Tolcoolollar	Wild Wolders
Description (Retail Display Packs)	Part No.
Torch Shrouds (Pack of 2) for semi-professional and	
No-Gas MIG Welders	8132050
0.6mm Welding Tips (Pack of 5)	8132020
0.8mm Welding Tips (Pack of 5)	8132030
1.0mm Welding Tips (Pack of 5)	8132040
Regulator to Convert No-Gas MIG to use with gas	8132000
Swan Neck	8132250
Replacement wire liner, suits all gas & no-gas MIGS	
up to & inc. 160T (Plastic)	8132170
Wire Liner Metal 2.5M	8132175
Wire Liner Teflon 2.5M	8132180
Swan Neck Wire Liner	8132185
Insulated Shroud (2)	8132055

### MIG Welding Wire (Blister Pack)

Description (Retail Display Packs)	Part No.
Mild Steel Wire Spool, 0.6mm (mini), Pack of 1	8132100
Mild Steel Wire Spool, 0.8mm (mini), Pack of 1	8132070
Mild Steel Wire Spool, 0.9mm (flux cored mini for No-Gas MIGS)	8132110
Stainless Steel Wire Spool, 0.8mm (mini), Pack of 1	8132090
Aluminium Wire Spool, 0.8mm (mini), Pack of 1	8132080
Aluminium Wire Spool, 0.8mm (mini), Pack of 1	81320

### **Standard Packaged MIG Wire**

Top quality precision wound (1.0 & 1.2mm only) MIG wire available by the pallet (at specially low prices) or packed in individual cartons. Conforms to BS2901 Part 1 1983 A18.

▶ Wide choice of sizes & weights. ▶ Individual & bulk quantity pricing.

### Gases (CO2, Argon, CO2-Argon Mix)

Now available singly or in boxes of 12.

<u> </u>							
Gas	For Welding	Part No.					
CO2 (390G) Recommended practical classics Feb 07 - Mild Steel							
CO2 (600G)* Best Buy Practical	Classics 07 - Mild Steel	6000643					
ARGON (60 Bar)	Aluminium/Stainless	6000661					
ARGON (110 Bar)*	Aluminium/Stainless	6000663					
CO2/ARGON MIX (60 Bar)	Thin Sheet Metal/Mild Steel/Stainless	6000660					
CO2/ARGON MIX (110 Bar)*	Thin Sheet Metal/Mild Steel/Stainless	6000662					
vo '	1.1 = 40/						

<sup>\*</sup>Same size as standard bottle but with 54% more gas.

### Gas Adaptor Hose (1M Long, Rubber, To BS5118/2)

•	
Description (Retail Display Packs)	Part No.
GRH1 - Large Gas Bottle Adaptor Hose (3/8" BSP)	6000497
GRH2 - Large Gas Bottle Adaptor Hose (1/4" BSP)	6000489

### Welding Headshields

Description	Part No.
Full welding headshield including Shade 11 glass - CWH1	6000675
ARC activated headshield - CWH5 See page 60 for full range.	6000674

### **Headshield Replacement Lenses**

Description (Retail Display Packs)	Part No.
Headshield Glass Packs (1 Dark Shade 8, 1 clear)	8132325
Headshield Glass Packs (1 Dark Shade 9, 1 clear)	8132330
Headshield Glass Packs (1 Dark Shade 10, 1 clear)	8132335
Headshield Glass Packs (1 Dark Shade 11, 1 clear)	8132340
Replacement lenses not suitable for CWH5, CWH6 & CWH7	

### **Anti-Spatter Spray**

Description	Part No.
300ml Anti spatter spray for use	
with MIG & TIG welders	6000715

									Flux
Wire Type		Mild	Steel		Stainless Steel Aluminium				Cored
	0.6mm	0.8mm	1.0mm	1.2mm	0.6mm	0.8mm	0.6mm	0.8mm	0.9mm
Spool Size	Part No.	Part No.	Part No.	Part No.	Part No.				
Mini (1 pack)	6000641	6000481	Χ	Χ	Χ	6000498	Χ	6000483	6000664
5Kg (1pack)	6000476	6000475	Χ	Χ	Χ	Χ	Χ	Χ	6000666 <mark>†</mark>
15Kg (1pack)	3050530	3050522	6000485*	6000487*	Χ	Χ	Χ	Χ	Χ



### **Industrial MIG Accessories**

Description (Retail Display Packs)	Part No.
Swan Neck	8132290
Shroud	8132280
0.6mm Tip (Pack of 5)	8132260
0.8mm Tip (Pack of 5)	8132270



exceptional value for money.

- Variable amperage control for precise welding power regulation.
- Safety thermal cut-out protects against overload.
- All units supplied with face mask (with BS679 lens) welding and earth leads, wire brush/pick and full operating instructions.

### Turbo Arc WELDERS CW145TN-190TEN 'Ideal for DIY and Automotive Workshops'

These high quality professional 'fan cooled' arc welders offer full 35 -180 amp performance, and are ideal for professional/industrial use, general repairs and light fabrication.

### Turbo Arc Industrial Welder - CW235TEN

This high quality professional arc welder is highly efficient due to its turbo fan cooling system. Ideal for tough daily use in automotive & maintenance workshops.

Easi-Arc DIY/Semi-Professional									
Model	105N	2 115N	3 160N	4 190N					
Min/Max Amps	40-100	30-110	40-150	50-185					
Electrodes Dia (mm)	1.6-2.5	1.6-2.5	1.6-3.25	1.6-3.25					
Open Circuit Volts	48	48	48	48					
Input Voltage/phase	230/1	230/1	230/1	230/1					
Av. Input Power kw	2.5	2.5	2.80	4.0					
Dims (LWH) mm	270x175x275	370x215x290	370x215x290	370x215x290					
Weight kg	11.5	12	14.5	17					
Part No.	6010972	6010974	6010976	6010978					

Fan Cooled A  CW145TN	rc Profession CW145ND (Dual Voltage)	al/Industrial 6 CW165TN	CW190TEN	CW235TEN
40-140	40-140	45-160	35-180	40-200
1.6-3.25mm	1.6-3.25	1.6-4.0	1.6-4.0	1.6-4.0mm
48	48	48	48	48
230/1	230/110v	230/1	230/1	230/1
3.5	3.5	4	4.5	5
410x250x310	410x250x310	500x260x340	500x260x340	440x280x320
18	18	23	25	29
6010605	6010600	6010610	6010742	6010237

### **Professional ARC Welders & ARC/TIG Inverters**

300TE

### 🕧 - 🙆 Professional Arc Welders

Top quality professional arc welders ideal for tough daily use in automotive and maintenance workshops for all types of metal fabrication, repair and maintenance work. All units feature:

▶ Variable amperage control. ▶ Safety thermal cut-out protects against overload. Drough metal casing. Accessory kit, comprising face mask welding and earth leads, wire brush/pick. ▶ Complete with wheels and handle. ▶ Turbo fan cooling on all models.

Welding electrodes - bulk packs							
Pack weight	Size	Part No.					
1.8kg	1.6mm	3050550					
2.0kg	2.0mm	3050555					
2.1kg	2.5mm	3050560					
2.5kg	3.25mm	3050565					
Mixed Pack							
1.6, 2.0, 2.5, 3.25mm							
(30 of each)		3050570					


### 🕞 - 🗐 85-150 Amp ARC/TIG Inverters

Low amp operation - ideal for TIG welding, auto bodywork and thin sheets of mild and stainless steel.

- Arc welds rutile, low hydrogen and stainless steel electrodes > Variable amperage control Turbo fan cooling
- Automatic short circuit protection
- ▶ Electronically DC output ▶ Light and portable > Tough ventilated steel casing
- ▶ Carry strap ▶ Supplied with arc kit (electrode holder, earth clamp, head shield & pick/brush) in handy carry case.



1 260TE



AT150



Items





Variable Amperage Control

6 AT130



Turbo Fan Cooling On All Models

350TE

8mm, Pack of 2 - Part No. 8132720.



Required for TIG welding.

Part No. 6010840



Items 6 is Required For Tig Welding With The AT 100, AT 130 & AT 150



Items 5 - 9 Supplied With Arc Kit (Electrode Holder, Earth Clamp, Head Shield & Pick/Brush) In Handy Carry Case

(F) ARC/TIG135

ARC/TIG13	1
-----------	---

Includes Electrode Holder

with Lead & Earth Clamp

		Max			Input	Dims		
	Min/max	electrodes	Open circuit	Volts/	Power	(LxWxH)	Weight	
Model	amps	mm	volts	phase	kw	mm	kg	Part No.
AT100	5-85	1.0-2.5	80	230/400/1	2.5	210x120x180	3	6012235
AT130	5/130	1.0-3.25	80	230/400/1	3.1	270x120x180	4	6012240
<b>☑</b> AT150	5/150	1.0-4.0	80	230/400/1	4.8	270x120x180	4.5	6012245
3 ARC/TIG135	30-130	3.25	80	230/400/1	5.4	285x120x220	4.3	6010790
ARC/TIG131	5-130	1.5-4.0	80	230/400/1	5.7	313x152x200	5.5	6012230



Sold separately. Part No. 8134140







	Model	Input	Max absorbed Power	Rating Power	Max Welding Thickness	Dimensions (mm)	Weight	Part No.
0	CSW6T	230v/50Hz	6 kw	1.2 kw	1+1mm	440x110x185	11.0kg	6030005
2	CSW13T	230v/50Hz	13 kw	2.3 kw	2+2mm	440x110x185	11.3kg	6030010

# 

Throat (mm)

120mm

250mm

500mm

120mm

350mm

350mm

120mm

6030111

6030113

6030115

6030117

6030119

6030121

# 13 - 12 Spot Weld Drills (Cutters) CHT467 & CHT468

Double-ended cutting blade assures extralong life. ▶ Spring loaded centre point guides cutter crown onto spot weld. ▶ Fine adjustment of cutting depth by allen screw. ▶ Suitable for air & electric drills.

**CHT467** 3/8" **CHT468** 5/16" Part No. 1801467. Part No. 1801468.



# Part No. 6030105 6030107 6030109 For secure handling of fabrication & we





Portable microprocessor controlled resistance-welding machine. Automatic adjustment of welding time and current according to thickness of chosen welding material. Continuous and pulsed operation settings. Pressure on arms adjustable from 40kg to 120kg (with arm length of 120mm). Part. No. 6030010.

### **3 Edge Setters - CES1/2**

Useful for creating a shallow lip along sheet metal edge, enabling flush joints to be made.


CES1 Edge setter & hole punch combined. Part. No. 7630075.

CES2 Edge setter. Part. No. 7630076.

# Door Lock Plate Repair Tool - CDL1

Described Suitable for use on all Vauxhall, BMW, Ford, Peugeot, Japanese models & the Volkswagen Golf/Passat. Described Poverall length 220mm.

Part No. 7652010.



### 1 Adjusting Tool - CDT1

To repair/re-shape angled edges found on the door lock mounting plate. Jaw width 10mm.

Overall length 220mm.

Part No. 7652020.



Items

13 PRO175



PRO177



Welding Gauntlets tested to CE Cat 2 standard Heavy Industrial, Gas and Arc Welding. One size fits all. Sold as a pair.

Part No. 8133490.

Description

'L' for spot welder

'L' for spot welder

'L' for spot welder

'L' for spot welder

U 'L' for spot welder

(Difficult) Position

**Electrodes - Clamp** 

Ext. Profile Electrodes


Int. Profile Electrodes



### **Welding Apron**

- Size 610x915mm.
- Manufactured from tough protective leather.
  Part No. 6000920.





### **Plasma Cutters & Welding Generators**



Slices cleanly through mild/stainless steel, aluminium, & copper.

▶ Easy to operate – ideal for autobody repairs ▶ Much faster than oxy-acetylene cutting, no need for gas cylinders ▶ Pilot arc torch gives instant cutting, even on painted surfaces ▶ With professional torch, earth lead & air filter/regulator ▶ Plasma King 20Ci has built in air compressor ▶ No need for air supply

🔼 Plasma King 55 Plasma King 55 Easy to operate - ideal for autobody repairs, metal recycling etc. Much faster than oxy-acetylene cutting, no need for gas cylinders. Pilot arc torch gives instant cutting, even on painted surfaces. Requires only compressed air and electricity supply. With professional on/off torch, earth lead and air filter/regulator. 3 Plasma King 30SI Slices cleanly through mild/stainless steel, aluminium & copper Pilot arc torch gives instant cutting, even on painted surfaces With professional on/off torch, earth lead & air filter/regulator 🚱 Plasma King 30SI

	Volts/	Input	Cutting	Cutting depth on mild steel/	Compressed	Air	Weight	Dims.	Part
Model	phase	current	current	aluminium	pressure	req.CFM	(kg)	(LxWxH)mm	No.
1 Plasma King 20Cl	230v,1ph	25A	25amps	6mm	Inc. Built-In Air	Compressor	16	525x175x345	6016020
Plasma King 55	230v,1ph	31A	40amps	8mm	5.2-5.7 bar	4cfm	50	580x456x710	6016001
3 Plasma King 30SI	230v,1ph	21A	28amps	10mm	4-5bar	3.5cfm	9	360x155x320	6016010

### Welder Generator & Trolley - WH215

Plasma King 20Cl Plasma Cutter

Versatile and mobile arc welder with auxiliary power output for operating power tools and lighting, independently on site.

Honda GX390 air cooled petrol engine ensures reliability and long life.
Recoil Start Method. Max. Output 200Amps (6.5KVA@230v, 4KVA@115v).
6.5ltr Fuel Tank. Fuel consumption @ 75% power 2.15 litres.
Noise level 72dB(A)@7M.
Dims. LxWxH 945x690x685mm.

Weight: 88kg.



Part No. 8130355.

5 Metre Welding Cable Kit for WH215.

# **6** Welding Screen - WS1

Measuring 2m x 2m this standard portable screen includes orange curtain. Weight 8Kg.

Part No. 6000810.

(6) WS1

# Heavy Duty Welding Screen - WS2

This heavy duty mobile screen includes heavy gauge (30 x 30 x 2mm) rectangular/round steel frame coated with tough grey enamel finish.

▶ 4 castors (2 with brakes) allow easy movement around the workshop. ▶ Measuring 2m x 2m this screen includes an orange curtain (2100 x 1600mm).
Weight 18Kg. Part No. 6000820.

### Replacement Screen - WC1

Measuring (WxH)1300x1800mm, two of these curtains are required as replacement for each of the screens. Supplied individually, these curtains include 50mm wide seam, 7 strong eyelets with suspension rings and snap fasteners. Weight 1.8Kg.

Part No. 6000900.



WS2



### Welding Accessories & Consumables

### - 3 Arc Activated Headshields

- Professional headshields that give eye protection to EN379
- Activates instantly when arc is struck
- Manually adjustable between dark shades DIN 9 to DIN 13
- Suitable for Arc, Mig, Tig & Gas
- CWH7 headshield includes 'Hot Rod' style flame design

### **Automatic** Arc -Activated







Model No	Light Shade	Dark Shade	UV/IR Protection	Weight	Order Code
① CWH5	DIN 4	DIN 9 – 13	DIN 13	0.5kg	6000674
2 CWH6	DIN 4	DIN 9 - 13	DIN 16	0.48kg	6000671
3 CWH7 (Flame)	DIN 4	DIN 9 – 13	DIN 16	0.48kg	6000672

# □ CHT102 **Piece**

### (5) 'C' Clamp Set - CHT102

3 piece set contains 6", 11" & 18" locking 'C' clamps. With adjustable tension.

Part No. 1800102.

### 6 2 Piece Magnetic Clamp Set

Powerful magnet holds work at correct angle when welding at 45° or 90°. 2 clamps per set. Part No. 1800117.



(75mm). Welding up to 5/16" (8mm). ▶ Standard <sup>3</sup>/8" BSP connectors. Weight 7kg. Part No. 6000670.

welding, cutting, soldering and brazing. Complete with welding and cutting torches, 3 welding nozzles, 3 cutting nozzles, mixer,

oxygen and acetylene regulators, 2 gas

tip cleaners and sparklighter, plus tough

moulded carrying case. Dutting up to 3"

hoses with fittings and flashback arrestors,

(4) CGW1

### CHT103 Lock Welding Clamps - CHT103

3 Piece locking and welding clamp set. Comprising 8" locking - grip bending tool, 9" welding clamp and 11" locking 'C' clamp. all with adjustable



### **Ⅲ** Gas Regulators Top quality regulators for use with any of our Mig Welders\*. \*Large gas bottle adaptor, Part No. 6000497, will be required if using these regulators with MIGs up to 150amp.

**Also for A	rgon/CO2 mix.		
Model	Description	Туре	Part No.
IR1A	Single Gauge	Argon**	8134060
IR2A	Twin Gauge	Argon**	8134070
IR1C	Single Gauge	CO2 only	8134090
IR2C	Twin Gauge	CO2 only	8134100
Adaptor -	Argon bottle to 0	O2 regulator	8134130

### 🕡 Adjustable Magnetic Clamp - ET129

As above but holds work for welding at any angle. 1 clamp per pack. Part No. 1700245.



Magnetic Square With On/Off Switch - CHT573

Achieve a 90° or 45° angle. Suitable for angle, round or square stock. Part No. 1801573.



Includes On/ Off Switch

### Oxygen/Acetylene Hose

5m and 10m Oxygen/Acetylene Hose with fittings (size 3/8").

Safety standard BS5120; 19787/EN559: 1994.

5m - WHS5M. Part No. 3125500. 10m - WHS10M

Part No. 3125510.



### 12 Flashback Arrestors

An essential in-line safety device for use where acetylene and oxygen are

combined for the purpose of welding. Fits directly to the oxygen or acetylene regulator to prevent any flame from reaching the bottle as a result of flash-back.



Fits Directly To The Regulator For In-Line Safety



Description	n Size	Part No.
Oxygen	1/4" BSP	8132315
Gas	1/4" BSP LH	8132320

### 1 - 5 Battery Chargers

Ideal for charging lead acid batteries these chargers all feature:

Protection against output short circuit, reverse connection & thermal overload. Double insulated construction.

Tough robust non-conductive casing.





	Max. Charge		Charge/Volts	Charge	Dimensions	Weight	Part
	Model	Amps	(Battery Type)	Indicator	LxWxH (mm)	kg	No.
0	CC40	2.7	12	LED	187x154x85	1.65	6266100
2	CC60	4.0	12	LED	187x154x85	1.65	6266105
3	CC80	6.0	6 or 12	AMMETER	165x110x275	2.55	6266110
4	CC120	8.5	12	AMMETER	185x100x123	2.55	6266115
6	AC70	4	12	LED	174x174x100	2.15	6266200

### Auto Trickle Charger - ATC12V

12v fully automatic battery charger ideal for charging motorcycle batteries or for trickle charging car/van batteries.

- Ideal for lead acid and sealed maintenance free batteries.
- LED charging indicator.
- ▶ Full self resetting protection against misuse & incorrect connection.
- Input: 230v AC 50Hz.
- Dutput: 0.5A DC 14.2V (Max. Continuous).

Part No. 6266010



### 6 12v, 7Amp Automatic Battery Charger - AC70

Fully automatic 12V battery charger ideal for maintenance-free and 'sealed for life' batteries. Gives the safest, most consistent charge possible.

▶ LED's indicate charging status. ▶ 3 mode microprocessor controlled charging. Automatic re-set between modes as battery status requires. ▶ 30% more efficient than conventional charger. ▶ When connected can provide continuous "topping up" to the battery. 2 second delay on

connection to avoid sparking. Duitable for deep cycle electric vehicle batteries. Part No. 6266200

### 6/12v Battery Tester - CVT1

Ideal for cars, vans HGVs and agricultural vehicles.

Tests state and condition of 6v and 12v lead acid batteries. Dompact and portable, ideal for motor dealers, garages and fleet use. I Strong steel construction with integral carry handle and clamp holders. Heavy duty insulated clamps.

Easy to use - no sparking.

▶ Testing can be carried out in-situ on most types of vehicles.

Weight 1.4Kg.

Part No 6260100





### 12v DC 1/2" Drive Impact Wrench - CIR13C

Ideal for fast removal of stubborn wheel nuts/studs. Weighing only 2.4kg, complete kit can be carried and stored easily in car boot. Dean be connected directly to car battery using battery clips, alternatively using the cigarette lighter socket. 2 double ended CIR13C sockets: 17-19

& 21-23mm.

Maximum torque: 125 lbs/ft. Part No. 4500610





### Battery Tester - CBT500

Ideal for cars, vans, HGVs and agricultural vehicles.

- 12v/500Amp adjustable load.
- Tests 12v batteries up to 160Ah.
- Large dual meters battery voltage and load current.

Heavy duty insulated clamps with heavy gauge solid copper stranded cables.

Colour coded temperature compensation pass/fail display.

- Weight 4.7kg.
- 1M connecting cable.
- Dims (LxWxH)







### 1 - 7 Powerful Starter/Chargers

Unbeatable value for money, these high performance top quality Starter/Chargers are ideal for a wide variety of applications from DIY to motor dealers, fleet operators, farmers etc, and are capable of starting most automobile engines - even with a flat battery. (Note: as a general rule – the larger the engine the higher the required boost amps).

▶ Multi position charge regulator. ▶ Ammeter to show charging amps. ▶ 230V, 1 Phase operation.

Complete with overload protection - on charge only, not boost. Copper leads and full instructions.

		Max. Charge	Max Boost	Boost Charge	Dimensions	Weight		
	Model	(amps)	(amps)	(volts)	LxWxH (mm)	kg	Part No.	
C	BC100N	15	100	12	130x173x240	4.0	6210101	
E	BC520N	50	510	12/24	425x275x650	25.0	6261080	
E	BC210N	25	200	12/24	215x215x300	12.0	6261035	
0	BC320E	35	310	12/24	425x275x650	20.0	6230500	
E	BC120N	15	120	12	215x215x300	9.0	6261005	
0	BC410E	35	400	12/24	250x270x440	18.0	6240100	
E	BC130N	15	120	12	280x175x280	7.4	6261010	4

### 8 - 10 Professional Booster Cables

Top quality for general through to heavy duty commercial use. Copper clad aluminium cables, durable PVC cables with robust clamps.

				Max amp	)
Model	Engine Cap. Petrol Itr	Length M	Cable Size	Cable rating	Part No.
CJL25D	2.5	3	$25 mm^2$	220	7631100
O CJL41D*	5.5	3.5	$41mm^2$	350	7631105
CJL54D*	7	4.5	$54mm^2$	480	7631110
*Engine Cap	Diesel CJL	41D up 1	to 3 ltr, C	CJL54D u	p to 4 ltr

Supplied In Handy Carry/Storage Bag With Full Instructions



4

BC130N

# Heavy Duty Professional Engine Starter/Chargers

GARAGE EQUIPMENT

63



Model	Max Charge (amps)	Max Boost (amps)	Remote Start	Input (voltage)	Weight (kg)	Phase	Boost/Charge (volts)	Slow/Fast Charge	Trolley Mounted	Cable Storage	Dimensions LxWxH(mm)	Part No.
1 BC185N	20	180	No	230	21	1	12/24	No	No	-	260x300x770	6261020
BC200N	30	200	No	230	21	1	12/24	No	Yes	Yes	260x300x770	6261030
3 BC260N†	30	250	Yes	230	28	1	12/24	Yes	Yes	Yes	320x490x730	6225053
BC335†	50	300	Yes	230	32	1	12/24	No	No	Yes	320x490x730	6235055
6 BC420N†	60	400	Yes	230	38	1	12/24	Yes	Yes	Yes	320x490x730	6261065

† Require non domestic supply



Ideal for professional & hobby use.
Measures:

- DC volts (0-500v).
- DC current (0-10 amps).
- Resistance (0-20MΩ).
- Dwell angles (3-12 cylinders).
- ▶ RPM (0-10,000 rpm on 3-12 cylinders).

### Includes:

Auto polarity indicator, diode test & audible continuity test.

Integral stand, test probes & battery. Part No. 4500480.

Ideal For Multi-Testing A Variety Of Automotive Electrical Systems



CA500

### Battery & Alternator Tester - CA600

Ideal for use on cars and vans

A quick, easy method for checking the condition of your car battery and alternator charging voltage

LEDs light up showing the condition of the battery and state of the alternator

Tests 12v batteries

Part No. 4500090



See Pages 48-49 For Our Full Range Of Multimeters, Testers & Detectors.





2 Professional Jumpstart 1000 12v Engine Starter

Starting boost output of 400A and Peak output of 900A. 17Ah 12v battery. Starts petrol and diesel engines upto 3 ltrs. High capacity battery with built-in 5 bulb lamp for an extra bright work light. LED battery status indicators. Audible incorrect polarity and low battery alarm Includes 230V mains charger and 12V adaptor for in-vehicle charging. Gripped carry handle and booster cable storage facility. Weight: 9Kg Part No. 6240040

Built-In 5 Bulb

Lamp For An Extra Bright Work Light

		Dependent on	battery status
Model	<b>1</b> JS1224	② JS1000	3 JS1010
Starting Boost (12v/24v)	1000A / 500A	400A / _	400A / _
Peak Amps (12v/24v)	2000A / 1000A	900A / _	900A / _
Engine Start Size Petrol*	Upto 6ltr	Upto 3ltr	Upto 3ltr
Engine Start Size Diesel*	Upto 3ltr	Upto 3ltr	Upto 3ltr
Battery 12v	22Ah	17Ah	17Ah
Battery 24v	22Ah	_	_
Weight	16kg	9kg	9kg
Part No.	6240045	6240040	6240035

Starts petrol and diesel engines upto 3 ltrs. Built-in 12V air compressor for tyre inflation upto 300psi. Flexible hose with snap on tyre valve connector, 2 nozzles and needle adaptor. Description 5 bulb lamp for an extra bright work light Audible incorrect polarity and low battery alarm Description 230V mains charger

and 12V adaptor for in-vehicle charging Weight: 9Kg

Part No. 6240035

### Jump Starts (with top quality long life battery)

The Clarke 12v JumpStart® range provides essential home, garage and road side assistance. Each model is fully portable and has a multitude of handy features in addition to providing a high powered start: Description Maintenance free, high capacity battery. Description Built in work light for roadside repairs or emergency situations. Description Power supply for operating 12v equipment, mobile phones, worklights, etc. Description Carry handle and booster cable storage facility. Description leads and heavy duty clamps. Description 230v mains charger and 12v adapter for in-vehicle charging. Description Audible incorrect polarity & low battery alarm on 4000 model.

JumpStart® 910 has the additional benefit of an air compressor for tyre inflation: Max pressure – 240psi. Graduated pressure gauge.

Flexible hose with snap on tyre valve connector, 2 nozzles and needle adapter.

JUMPSTART 4000 HAS POWERFUL 1500

PEAK AMPERAGE AND A STARTING BOOST OF 700 AMPS

JUMPSTART® Is A Registered Trade Mark Of Clarke International Ltd. Don't Be Confused By Inferior Imitations With Poor Quality Lightweight Battery & Short Leads

Weighs 17kg

### **HEAVY DUTY**

Includes extra power battery for starting bigger engines & longer use as a power supply

Best Buy

MICH CARAVAN

JumpStart 4000

WITH AIR

2 JumpStart 910

3 JumpStart 900



All Items Feature Built-In Light & Charging Level/Battery Condition Meter

JUMPSTART® 900, 910
& 4000 with

QUALITY

BATTERIES FOR

LONGER LIFE &
EXTRA DUTY


Longer Leads for easier use All models 1M to clamps.

**Best Value** 

# **WHICH CARAVAN**

JUMPSTART® 910 Includes a cigarette lighter plug for powering 12v equipment such as power tools, mobile phones, work lights, radios etc.

> JUMPSTART® 910 Includes Quality 12v DC Air Compressor



Model	Starting	Peak	Cable	Engine Sta	arting Size	Weight	Part No.
	boost	amps	length	petrol	diesel	•	
<b>1</b> 4000	700	1500	1m	4 - 6ltr*	2.5 - 4ltr*	17kg	6240030
2 910	400	900	1m	2.5 - 3ltr*	2 - 3ltr*	9.5kg	6240020
900	400	900	1m	2.5 - 3ltr*	2 - 3ltr*	8.2kg	6240010





### **Hydraulic Trolley Jacks**

### 1.25 Tonne Lightweight Aluminium **Trolley Jack - CTJ1250A**




High quality aluminium construction ideal for sports and race cars. Features extra low saddle and frame. Rubber contact pad, helps prevent damage to the vehicle. Simple twist lock/unlock valve for added safety. Lightweight design

only 10.3kg. Duperb blue anodised finish.

Tonnes Min Max **1.25 CTJ1250A** 1.25 79mm 376mm

Dimensions Weight Part No. LxWxH mm kg 533x280x203 10.3





### 🔼 2 Tonne DIY Trolley Jack - CTJ2B

Features: Welded castor supports Integral carry handle

▶ Simple twist lock/unlock valve ▶ One piece handle with comfort grip

Automatic overload protection.



### 2 Tonne DIY Trolley Jack With Tough **Moulded Carry Case - CTJ2MB**

Our CTJ2B jack supplied in its own handy carry/storage case, ideal for keeping safe and tidy in the boot of a car or in the

home workshop/garage.

**Supplied In Tough** Part No. 7623040. Moulded Case





3 Strokes

### 2 Tonne Trolley Jack - CTJ2L



### 2 Tonne Quick Lift Trolley Jack - CTJ2Q

Just three strokes raises this jack to vehicle contact point. Ideal for mobile service and motor sport use.

▶ Reinforced one-piece frame for extra strength. ▶ Built in by-pass system prevents overloading. Donvenient carry handle. Part No. 7621805.



### 6 2 Tonne Quick Lift Trolley Jack With Tough Moulded Carry Case - CTJ2QM

Our CTJ2Q jack supplied in its own handy carry/storage case for safe, tidy storage and transportation.

Part No. 7621810.



LIFT	ToV	ehicle Cont	act Point
	14		
			_

Supplied In Tough Moulded Case

🕞 CTJ2QM

		Capacity	Saddle	Height max	k. Dimensions	Weight	
Model	Description	tonnes	min.	(mm)	LxHxW (mm)	kg	Part No.
CTJ2B	DIY Trolley Jack	2 tonne	130mm	208mm	452x188x151	8.5	7623035
CTJ2L	Trolley Jack Long	2 tonne	125mm	385mm	530x215x140	11.1	7610250
CTJ2MB	DIY Trolley Jack & Case	e 2 tonne	130mm	208mm	452x188x151	10.5	7623040
CTJ2Q	Quick Lift Jack	2 tonne	135mm	365mm	525x190x155	11.1	7621805
⑥ CTJ2QM	Quick Lift Jack & Case	2 tonne	135mm	365mm	525x190x155	12.3	7621810



**Professional/Heavy Duty Hydraulic Trolley Jacks** 




A single stroke instantly raises the saddle to vehicle contact point. You can't get quicker than this. Saves valuable time, ideal for mobile service and fast fit centres & motorsport.

- Is Simple foot pedal instant lift.
- Extra strong base construction.
- Heavy duty wheels and castors.
- Single piece hydraulic unit.
- Overload protection.



### Ideal for professional garage/workshop use, this jack features: ▶ Single piece hydraulic unit for reliability Heavy gauge base construction Extra strong, long 2 piece handle with positive twist **CTJ3000G** locking & release mechanism Heavy duty wheels and castors Automatic overload protection.



3 Tonne Professional Garage

Jack - CTJ3000G

3 Strokes To Vehicle Contact Point



CTJ3000QL



### 3 Tonne Instant Lift Professional Garage Jack - CTJ3QLG

A single stroke instantly raises the saddle to vehicle contact point. You can't get quicker than this. Saves valuable time, ideal for mobile service and fast fit centres & motorsport.

- ▶ Simple foot pedal instant lift. ▶ Extra strong base construction. Heavy duty wheels and castors.
- Single piece hydraulic unit. Doverload protection.







			Saddle	Height	Dimensions	Weight	Part
Model	Description	Capacity	Min	Max	LxWxH (mm)	kg	No.
①CTJ2001G	Pro Garage Jack	2 Tonne	131mm	376mm	597x345x258	34	7623045
CTJ3000G	Pro Garage Jack	3 Tonne	120mm	520mm	630x340x185	37.4	7623030
3 CTJ2QLG	Pro Instant Lift	2 Tonne	135mm	485mm	650x345x190	31.9	7621815
CTJ3000QL	Quick Lift Jack	3 Tonne	195mm	520mm	595x190x195	15.9	7623025
⑤CTJ3QLG	Pro Instant Lift	3 Tonne	145mm	520mm	640x345x180	38.1	7621005

### **Heavy Duty/Commercial Garage Jacks**





### 2 2 Tonne High Lift Long Chassis Trolley Jack - CTJ2GLC

The extra long chassis & high lift on this jack makes it ideal for use on 4x4 and commercial vehicles.

Foot pedal operation to contact point. Extra high lift for 4 x 4 and high clearance vehicles. Long handle for easier positioning under large vehicles.



### 🗿 - ❹ 5 & 10 Tonne Long Chassis Jack CTJ5GLB & CTJ10GLB

An extra long chassis makes this jack ideal for professional use on commercial vehicles. Pedal lift for quicker action Twist lock/unlock valve on the end of the

handle for easier use Rubber pad for soft contact against vehicle



ow Profile Cars

### **Hydraulic Oil**

Ideal for use with all of our hydraulic equipment.

1 Litre

Part No. 3050830.

5 Litre

Part No. 3050835.





F CFC2000



### Heavy Duty 2 Tonne Large Folding Crane - CFC2000

The CFC2000 workshop crane offers rugged construction combined with the convenience of a compact, space saving folding crane. As such, it is ideal for use by both DIY car enthusiasts and professional garages. A three stage extending jib offers excellent lifting range whilst long legs, heavy-duty castors and wheels, ensure ample stability and manoeuvrability.

- ▶ Lifting capacity of 1500kg to 2000kg in three stages ▶ Maximum lifting height 2750mm Maximum jib length 1700mm (stage three)
- Leg height 205mm Doverall leg width 1110mm outside, 1000mm inside

Supplied with lifting hook

Part No. 7611020.

Model

**○** CTJ2LP

CTJ2GLC

3 CTJ5GLB



### 🔱 - 🔱 Professional Heavy Duty Bottle Jacks To Suit All Applications (2 - 20 Tonnes)

Built for tough daily use in garages and industrial workshops these quality bottle jacks combine proven reliability with exceptional value for money:

▶ Tough cast iron bases include screw in components for easy maintenance. ▶ All models include quality chrome plated ram with additional screw in/out height adjuster. ▶ Supplied with two piece pumping handle. ▶ Fully tested to latest European Standards. ▶ Automatic overload protection.

		Jack h	eight		
Model	Capacity	Min	Max	Weight kg	Part no.
CBJ2	2 Tonne	155mm	295mm	3.0	7620005
CBJ4	4 Tonne	190mm	385mm	3.8	7620010
G CBJ6	6 Tonne	195mm	405mm	5.5	7620015
CBJ8	8 Tonne	200mm	415mm	6.2	7620020
3 CBJ10	10 Tonne	200mm	420mm	6.9	7620025
© CBJ12	12 Tonne	210mm	435mm	8.0	7620030
CBJ20	20 Tonne	240mm	490mm	14.0	7620035



# Farm Jack/ Vehicle Jack - CFJ48

This extremely versatile jack is designed to lift, pull & push equipment & machinery up to 2000kg.

- Extra long jacking beam
- makes operation easy.

  Max working height
- 1090mm. Min height 100mm. Min load for lowering - 50kg. Large
- foot, helps to spread load.

  Ratchet system for safety.
- Can be used for quick lifting off-road vehicles. Weight 13.6kg.

Part No. 3400300

Max Working Height 1090mm



CFJ48

.

### **Professional Hydraulic Presses**



	Quick	Two	Capacity	Bed	Bed to Ram	Ram	Ram		Over	all dimensi	ons(mm)		Weight	Part
Model	Return	Speed	(Tons)	Gap (A)	Width (B)	Max(C)	Stages (D)	Travel (E)	Dia.	Width (F)	Depth (G)	Height (H)	Kg	No.
CSA10B	-	-	10	132	360	360	100	200	42	545	305	985	52	7614000
CSA10F	-	-	10	85	415	920	155	200	42	700	470	1525	66	7613010
3 CSA15F	-	-	15	120	540	930	100	130	65	910	605	1865	125	7614051
4 AHP15	<b>/</b>	~	15	175	550	970	80	155	45	870	655	1920	150	7615100
<b>5</b> AHP25	<b>V</b>	~	25	175	630	1030	80	160	50	970	655	2050	170	7615110
6 AHP50	~	<b>V</b>	50	210	780	1070	110	150	70	1150	645	2280	370	7615150

### **Engine Stands, Arbor Presses, Spring Compressor & Body Straightener**



# 2 Heavy Duty Engine Stand

This heavy duty professional engine stand with big 340kg capacity accepts a wide range of engines up to V8's and light commercials, as well as cylinder heads and transmissions.

▶ Rotates through 360 degrees for maximum accessibility. The extra-wide, 4 wheel base with steel wheels gives added stability.

Complete with tool/parts storage tray. Dimensions (LxWxH) 1050 x 830 x 860mm. ▶ Weight 30Kg. Part No. 7610120.

Extra Wide 4 Wheel Base (Including Steel Wheels)Gives Added Stability



### 6 Heavy Duty Arbor Presses

Ideal for repetitive manufacturing processes, these cast iron presses include a rotating table with different size cut-outs.

Model	■ AP500B	AP1000
Throat Depth	117mm	140mm
Throat Height	112mm	138mm
Base LxW mm	240x103	270x129
Height	280mm	439mm
Capacity	1/2 Ton	1 Ton
Ram Size mm	17x17	23.6x23.6
Weight kg	9.3	15
Part No.	7615172	7615175

Will Fit Most Vehicles



\Ma: - b4

David

# Vehicle Body Straightener - CBT10

Offering the added flexibility of a left and right tilting anchor post, this heavy duty professional body straightener is supplied with round pivot bar and the full accessory kit shown, (including pump, ram and hose). Dimensions (LxWxH) 3610x820x1860mm.



4 10 Ton Tilting

### 7) - 🔞 Engine/Gearbox Supports

These heavy duty Engine/Gearbox supports are ideal for automotive workshop use. Designed for working on front wheel drive transmissions/ drive-shafts and as an aid for the removal of gearboxes and transmissions whilst supporting the engine.

Models are fitted with soft rubber shoes to prevent damage to vehicle bodywork. Fine adjustable screw mechanism allows accurate movement under load.

Max

N/1:...

Model	Wax. capacity	Win. width	width	Screw travel	weight kg	Part no.
CEC300	300kg	660mm	1420mm	210mm	14	7612905
3 CEC500	500kg	1020mm	1600mm	350mm	17.5	7612910
② CEC500	EC300			S-0-8		
	le co	Co J		8º0	3-00-0	9
Fully Adju	upports Ar ustable Ar	d S	<b>€</b> €0			

# **72** GARAGE EQUIPMENT

# Folding Hydraulic Engine/Workshop Cranes



		Lifti	ng capac	ity (kg)		Max. lift	Max jib	Height of	Overall w	idth to	Weight	Part
Model	Description	Stage 1	Stage 2	Stage 3	Stage 4	height (mm)	length (mm)	legs (mm)	Outside	Inside	kg	No.
Folding Cranes									(mm)	(mm)		
① CFC100	1 tonne folding	1000	750	500	250	2060	1170	150	1030	890	79	7611005
2 CFC1000	1 tonne large folding	1000	750	500	250	1920	1137	160	962	812	87	7611010
3 CFC500F	1/2 tonne folding	500	350	250	150	2400	1100	130	860	690	84	7610610
Heavy duty folding cra	ines											
CHC1000DF	1 tonne folding	1000	800	650	450	2400	1380	165	980	870	110	7611002

3 HDFC2

2000

HDC200



**HDC200** Rigid frame cranes for workshop use.

Heavy duty industrial models have double action pumps for faster lifting operation, and are suitable for garages, workshops and industrial applications.

Lifting pump handle accessed from rear.

**Build Quality Of** All Our Cranes Meets Latest EEC Standards 89/392 & En 292-2

F CFC2000

Shown With 4 Optional Load Leveller



## 2 Long Reach Crane - CFC1000LR


Ideal for lifting hard to reach engines and general workshop use.

Extendable front and rear legs for extra stability. Lifting pump handle accessed from side.

> Extendable Legs & Jib Ideal For Lifting Hard To Reach Engines

> > CFC1000LR

For Improved Access The Pump Action Lever Can Be Repositioned On Either Side & Angled 20°



Swivel Ram/Low Leg Crane - HDFC2

These lower leg height (only 85mm) cranes allow you to get underneath even the lowest of sports cars, and include a repositionable handle with swivel ram for superior lifting control. Folds for compact storage. Two additional wheels on the base for easy movement when folded.

### 500KG Load Leveller - CLL500

This precision load leveller features fine screw adjustment facility for precise levelling of awkward shape, hard to balance engines/gearboxes etc up to 500kg.

More accurate than crude peg-type levellers. Includes chains & hooks, as illustrated.

Can be used with most cranes. Dimensions (LxWxH): 730 x 139 x 175mm Weight: 6.6kg. Part No. 7630115.

A





The CFC2000 workshop crane offers rugged construction combined with the convenience of a compact, space saving folding crane. As such, it is ideal for use by both DIY car enthusiasts and professional garages. A three stage extending jib offers excellent lifting range whilst long legs, heavy-duty castors and wheels, ensure ample stability and manoeuvrability.

Lifting capacity of 1500kg to 2000kg in three stages Maximum lifting height 2750mm Maximum jib length 1700mm (stage three) Leg height 205mm Overall leg width 1110mm outside,1000mm inside

Supplied with lifting hook

For Fast, Easy Load Levelling



Charles STECTED

	Part No. 7611020.											
		Liftir	ıg capaci	ty (kg)		Max. lift	Max jib	Height of	Overall w	idth to	Weight	Part
Model	Description	Stage 1	Stage 2	Stage 3	Stage 4	height (mm)	length (mm)	legs (mm)	Outside	Inside	kg	No.
Swivel ram/Low leg for	olding cranes								(mm)	(mm)		
① HDC200	2 tonne HD	2000	1500	1000	600	3270	1970	220	1120	980	220	7612280
Long reach crane												
2 CFC1000LR	1 tonne long reach	1000	750	500	250	2400	1500	130	1020	830	119	7610660
Heavy duty folding cra	ines											
3 HDFC2	1 tonne	1000	800	650	450	2400	1380	85	980	870	110	7611310
5 CFC2000	2 tonne large folding	2000	1700	1500	-	2750	1700	205	1110	1000	165	7611020

1/2 TON

# 1 Heavy Duty 2 Stage Transmission 2 Adjustable Transmission Jack - 1/2 Ton CTJ500 Jack Head

This top quality two stage professional transmission jack is ideal for the garage trade for car and light commercial gearboxes etc.

- Heavy duty two stage hydraulic cylinder gives maximum 1850mm lift. Adjustable support cradle to accommodate awkward shapes and sizes.
- ▶ Safety chains for added security. ▶ Fully adjustable saddle has tilt and cross controls.
- Precise foot operated release control.
- Dimensions: (LxWxH) 1000 x 1000 x 933mm.



T CTJ500

**Includes Fully** 

Adjustable Jack **Head Saddle** 



Jack

This optional head unit fits our standard 1/2

adjustable saddle position with tilt controls

accommodate awkward shapes and sizes.

Ton Transmission Jack and provides


and adjustable support arms to

### 🔼 8 Gallon Oil Drain Cart - ODC8

Low entry cart for garage use. Ideal for commercial vehicle oil changes etc, with its large capacity.

Two castors, two fixed wheels and long detachable handle make this easy to move into position. Manual drain valve and suction evacuation valve to be used with a pump.

36.37 litre (8 gallon) capacity. ▶ Oil filter on



Weight 11.5kg. Part No. 3051470.

ODC8

COD70

### Transmission Jacks 1/4 and 1/2 Ton - CTJ25 & CTJ50

A useful addition to any garage or workshop.

Convenient foot pedal lifting. Heavy duty hydraulic cylinders. Variable release control.





### 2 Tonne Tripod Stand - CTS4000

Tripod frame for stability with screw height adjustment. Ideal for use as a transmission stand.

- Supporting capacity
- 2 Tonne. Minimum height
- 1240mm. Maximum support height - 2350mm. Weight 25kg.





€ CTS4000



### 70ltr Oil **Drainer** COD70

Gravity feed oil drainer with 2 metre discharge hose. Ideal for professional garage use, for clean collection, storage and disposal of waste fuel oil & other non-flammable oils.

- Air operated fast and safe tank emptying. Heavy duty castors, wheels and pull handle enable stable manoeuvring around the workshop. Dil level (tank capacity) indicator.
- ▶ Telescopic drain pan with filter grid.
- Pressure safety valve.
- Dimensions (LxWxH) 580 x 490 x 1570 (max height).
- Weight 35kg

Part No. 7630203.



- Hand operated pump is suitable for oil extraction only
- Ideal for use on motorcycles, generators, air compressors & lawn mowers
- ▶ 1.5 litre oil receptor cap ▶ Inc. vacuum pump, universal adaptor plug, 2 x transfer hoses (Lengths: 1m & 1.4m) & oil receptor
- Dims (LxWxH) 122 x 122 x 385 470mm Weight 0.5kg





# Rubber Matting, Foam Flooring & Grass Protector Matting

### 🚺 Six Piece Anti-Fatigue Foam Flooring

Interlocking foam tiles protect flooring & provide extra comfort when

standing or kneeling.

▶ Strong and durable it is ideal for use in workshops, garages, kitchens, living rooms, bars & gyms. ▶ Can be quickly lifted and re-laid. ▶ Checker plate design for increased grip. ▶ 6 tiles per pack. ▶ Includes highly visible yellow borders for safety purposes. ▶ Each tile has

- four detachable borders.
  Size: 610x610mm.
- Overs up to 2.23M² when used with borders. Part No. 3607000.



Grass Protector Matting - 900 x 900 x 16mm

Dual purpose matting produced from 100% rubber. Ideal for protecting grass in areas of heavy wear. Use on drives, car parks, caravan/camp sites and in gardens, gateways, paddocks etc.

▶ The shaped design allows grass to grow through the matting and can


be mowed over the top when secured.

Is also designed for use as a draining mat. Ideal for easy drainage behind the bar in pubs, clubs, restaurants and as a door entry scraper mat.

Dimensions 900 x 900 x 16mm.

Part No. 3607010.





### Rubber Matting - (Available In Ribbed, Smooth & Studded Surface)


Hard wearing rubber matting, available in ribbed, smooth or studded surface.

- Oil and grease resistant. Easy to clean.
- Protects surfaces and reduces noise.
- ▶ Provides impact protection. ▶ Increases slip resistance. ▶ Suitable for many applications including flooring, walkways and ramps, tool boxes, workbenches, shelving and drawer liners, vehicle and trailer floor lining.









2 mm	 3 mm
5	 .6
mm	 ШШ



	4	30mm	•	
3 mm				4.5 mm

Туре	Thickness	Size (WxL)	Colour	Part No.
Ribbed - Fine Fluted	3mm	915mm x 5M	Black	3606105
Ribbed - Fine Fluted	3mm	915mm x 10M	Black	3606115
Ribbed - Fine Fluted	3mm	1220mm x 5M	Black	3606110
Ribbed - Fine Fluted	3mm	1220mm x 10M	Black	3606120
Ribbed - Fine Fluted	6mm	915mm x 10M	Black	3606125
Ribbed - Fine Fluted	6mm	1220mm x 10M	Black	3606130
Smooth	3mm	1000mm x 5M	Black	3606205
Smooth	6mm	1000mm x 5M	Black	3606210
Studded - 20mm Stud Dia.	3mm*	1000mm x 10M	Grey	3606305
Studded - 20mm Stud Dia.	3mm*	1000mm x 10M	Black	3606310

<sup>\*</sup> Plus 1.5mm stud height

# 4 Air Operated Clutch & Brake Bleeding Kit - CHT637

Extractor siphons brake oil from the bleed nipple through a vacuum created by a compressed air supply. Brake bleeder refills oil carefully & quickly through simple connection.

- ▶ Ideal for bleeding brake and clutch systems quickly with no mess ▶ Can also be used for extracting engine oil, water etc. ▶ Automatic air inlet shut off function
- ▶ 2 litre pneumatic fluid extractor ▶ 1 litre brake fluid top up reservoir ▶ 2 extraction hoses ▶ Air consumption 5cfm ▶ Working air pressure 70 170psi ¾" BSP connector

Part No. 1801637.





### 1 4 Ton Hydraulic Body Repair Kit - CS4TK

The complete professional quality starter kit. With popular spreader wedge ram and a variety of time-saving attachments, this easy to use, keenly priced kit is supplied in a handy tough moulded case.

Weight 20.5kg.



### 10 Ton Hydraulic Body Repair Kit - CS10TK


Widely used for many years by professional body repairers. This kit is complete with heavy duty hydraulic pump, ram and wedge ram, plus a full range of accessories shown. Interchangeable with most other hydraulic body repair equipment, and supplied in a sturdy metal case.



### 10 Ton Hydraulic Pump Ram And Hose - CS10TKP

interchangeable between many of our 10 ton hvdraulic products, such as the 10 ton floor and bench presses, the 10 ton body repair kit and the 10 ton body straightener.

Weight 12kg. Part No. 7630060.





Ideal for tough daily use, this professional, portable and easy to use machine is suitable for both pipefitting and general fabrication.

Operates in both horizontal and vertical positions. Heavy duty steel construction throughout. Denote the Robust single piston hydraulic unit for powerful smooth operation. Dending capacity up to 180°. Dupplied with formers to suit pipes of normal bores as follows:

Nominal Bore	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Outside Dia.	27/32"	1 <sup>1</sup> / <sub>16</sub> "	1 3/8"	1 <sup>11</sup> / <sub>16</sub> "	1 <sup>27</sup> / <sub>32</sub> "	2 3/8"

Dimensions: (LxWxH) 620x570x175mm. ▶ Weight 43kg. Part No. 7610900.

### 4 10 Ton Hydraulic Pump - CAP100

This foot controlled, air operated 10 ton pump can be used with any of our 10 ton hydraulics to replace the hand pump unit, for complete hands free operation. Requires a compressed air supply producing 100 psi (4.1-6.9 bar). ▶ Rated pressure 10,000 psi, oil delivery 0.8cc/stroke.

CAP100

Fitted with safety hydraulic

pressure overload valve.

Weight 5kg. Part No. 7630100.

### 🜀 2 Ton Hvdraulic Puller Kit - CP2T

This compact 2 ton puller is used with the pump from our 4 Ton Body Repair Kit. Supplied complete with reverse V Blocks/chain hooks, pull clamps and rings.

Weight 6.5kg. Part No. 7630081.





### 🕡 5 Ton Hydraulic Puller Kit - CP5T

This powerful heavy duty 5 ton pull kit for professional crash repair work has claw hooks at each end to accept 3/8" (9.5mm) chain links. Use with the Clarke 10 ton hydraulic pump or the CAP100 Air/Hydraulic Pump.



### Wheel Dollies, Dolly Trolly, Seats Parking Barriers & Garage Rack



### Garage Rack - CGR1

Steel rack that is simple to fit to the walls of a garage for ceiling storage. The rack can be adjusted to different widths and can accommodate ladders, planks of wood, piping, scaffolding etc.

- Min/Max widths: 1900/3300mm
- Maximum load capacity: 120kg (evenly distributed over both rails)
- Weight: 6.8kg

Part No. 7628904







### Folding Parking Barrier - CPB1

Protect against theft, unwanted parking and restrict access to driveways. Surface mounted on concrete, asphalt, tile or brickwork. Quick and easy to operate

- ▶ 40mm diameter steel tube
- 2mm wall thickness
- Dims HxW (mm): 420x750
- Folds flat when not in use.

Part No. 7628902

### Mechanics Car Seat - CMS1

Robust steel framework with tough powder coated finish. Dil resistant vinyl covered seat cushion for added comfort. Four

swivel castor wheels with ball bearings for easy manuvrability. Dimensions:

(LxWxH) 380 x 360 x 380mm.

Weight 5kg Part No. 7630198.



### (iii) Workshop Swivel Stool - WSS 1

CERNS-BOOM

Ideal for use in all DIY and professional workshops. ) Chrome plated finish > 360° swivel action for easy adjustment whilst working Padded seat for comfort 140kg maximum capacity Dimensions: 530x730mm (WxH) Weight: 6.1kg Part No. 7630182





Supplied With Self Adhesive Reflector Stripes, Padlock With 3 Keys And Fixings

### 🚺 Adjustable Seat - CMS2

Height adjustable seat with 5 easy rolling castors for manoeuvrability and easy reach tool storage tray. Foam padded for maximum comfort. Height adjustable seat from 380mm-490mm. Seat swivels 360°. Dimensions: (DxH) 380 x 380mm (490max). Weight 7kg. Part No. 7630199.

CMS2



Ideal for fast tyre changing and general workshop, garage and construction use. High torque for loosening/tightening stubborn nuts. Heavy duty metal gears

and gear housing for extra durability. Includes forward/reverse facility and vibration reducing

comfort grip. Powerful 24v, 1.7Ah Ni-Cd battery 1/2" square drive Max torque delivery 450Nm Impacts per minute 2600

Speed (no load) 2000rpm Part No. 4500630

(IR450

Supplied With Carry Case, Side Handle, Ni-Cd Battery

And 1 Hour Mains Charger

Torque 450Ňm

Robust steel framework with tough powder coated finish. Oil resistant vinyl covered

2 1/2" Drive Electric Impact Wrench - CEW1000

Powerful impact wrench for heavy duty applications. Ideal for steel erectors, fitters, engineers and garage mechanics.

230v motor Max. torque 450Nm No load speed 2200rpm No load impact rate



3400ipm Part No. 6480300

**Includes Impact** Sockets: 17, 19, 21 & 22mm And Carry Case

High Torque 450Nm

**2** CEW1000

3 1/2" Drive Cordless Impact Wrench - CIR24 1 Hour Charlie Charge **Batteries** Heav Duty **Heavy duty 24v cordless** impact wrench with 200NM of torque.

Ideal for tyre changing & use in workshops, garages, body shops etc. Ergonomically shaped soft grip.

Conveniently located forward/reverse controls.

2 In 1 Folding Car Creeper/Seat

mechanics seat: ) Oil resistant vinyl covered padded back and headrest for maximum

comfort during long periods under the vehicle.

Ingenious split back design allows dual

applications either as a flat creeper or

Takes seconds to convert with one easy

movement (no tools required). > 7 swivel

Inc. 17,19, 21 & 23mm Chrome Vanadium sockets, 1 hour battery charger & 2 x 24v Ni-Cd Battery. Part No. 4500620.

CMC50

**Includes Carry** Case, Charger & 17/19/21/ 23mm **Impact Sockets** 

CIR24

### 12v DC 1/2" Drive Impact Wrench - CIR13C

Ideal for fast removal of stubborn wheel nuts/studs. Weighing only 2.4kg, complete kit can be carried and stored easily in car boot.

Can be connected directly to car battery using battery clips,

alternatively using the cigarette lighter socket.

2 double ended sockets: 17-19 & 21-23mm.

Maximum torque:125 lbs/ft. Part No. 4500610





**7** Twin Storage Trays

For Quick And Easy Access To Your Tools

TOOLS NOT

manoeuvrability. Adjustable head

> and back rest. Steel framework with tough powder

castors for easy

coated finish. Dims: (LxWxH) 1200 x 440 x 130mm

Weight 14Kg Part No. 7630191

CMC50

2 Functions In 1 TOOLS NOT

### padded back and headrest for maximum comfort during long periods under or beside the vehicle. Six swivel castor wheels for easy manoeuvrability.

Dim (LxWxH) Model Weight Part kg mm No. CMC36 920x430x110 7630187



CMC45



### **Towing Bars, Foot Pumps & Covers**



Ideal for secure towing of cars and light vans, these rigid steel towing bars are available with or without damper spring. Manufactured to EC standards.

- Overall Length 1828mm. Distance between hooks 1800mm.
- 2 Tonne Tow Bar TB-2S with Spring Damper Part No. 7630437.
- 2 Tonne Tow Bar TB-2 Part No. 7630435.



Steel framed foot pump with steel barrel.

- Fitted with 480mm flexible hose and thumb lock lever tyre connector. DApproved to EC Standard. Dauge graduated in psi (range 0-100psi) and Bar (0-7Bar). Includes pre-set indicator.
- Pump comes complete with cone-shaped nozzle for air beds, inflatable boats and bicycle valve adaptor. Weight 1kg. Part No. 7640250.



Twin Barrel Foot Pump - FP200

Durable polyester material

resistant to water & UV rays

condensation | Elasticated hem Protects against rain, sun, wind, smog, dust,


snow & ice ▶ Size: 2 x 0.9 x

1.2M Model No. MC90 Part No. 6471200.

Ventilation prevents

High performance foot pump with two steel barrels.

- Fitted with 565mm flexible hose and thumb lock lever tyre connector.
- Approved to EC Standard.
- Gauge graduated in psi (range 0-100psi) and Bar (0-7Bar). Includes pre-set indicator.
- Pump comes complete with cone-shaped nozzle for air beds, inflatable boats and bicycle valve adaptor. Weight 1.55kg. Part No. 7640260.



**Lightweight, Weatherproof Car Covers** 

Lightweight, weatherproof covers for protection of your vehicle. Tough outer layer with soft anti-scratch lining.

Stain resistant Includes storage bag Elasticated edges for good fit

Fits vehicles up to 4.3 metres long Model No. PCC170 Part No. 6471202.

Fits vehicles up to 4.8 metres long Model No. PCC190 Part No. 6471204.





Breathable Car Covers Breathable car covers with superior water resistance. Moisture evaporation leaves cover dry and stops mould and mildew.

- ▶ Prevents oxidation ▶ Super soft lining
- Protects from sun, dust, tree sap, pollutants and bird droppings
- Supplied with storage bag

### Medium

Fits vehicles up to 4.3 metres long Model No. TCC170 Part No. 6471206.

Fits vehicles up to 4.8 metres long Model No. TCC190 Part No. 6471208.



## Magnetic Protective Wing Cover

Storage Bag

Protects vehicle bodywork during maintenance work. Made from tough durable foamed PVC. Is Sleeved magnets hold the cover firmly in position. Wipe clean surface on both sides. Dimensions: (WxD) 960 x 450mm.

Part No. 7640625.



### 📵 2 Ton Tow Rope - TOW2

Suitable for towing vehicles up to 2000Kg

Manufactured to BSAU187. ▶ 4.5m long. coupling to coupling. Heavy duty zinc plated couplings. Part No. 7630430.



