

# Power Supply for DC drivers

## CLT-30

RoHS CE UL

Connects to one CL-2000, CL-3000, SS-2000 or SS-3000 model.



### Specifications

Model	<b>CLT-30</b>
Input	AC100-240V ±5% (47-63 Hz)
Output Voltage	LOW/Hi
Size (mm)	62x134x40 (H)
Weight (kg)	0.3
Power Cord Length (m)	1.8

## CLT-60

RoHS CE UL

Connects to one CL, SS or  $\alpha$  series driver. (except CL-9000 model).



### Specifications

Model	<b>CLT-60</b>
Input	AC100-240V ±5% (47-63 Hz)
Output Voltage	LOW/Hi
Size (mm)	88x210x52 (H)
Weight (kg)	0.83
Power Cord Length (m)	1.8

## LHT-30

RoHS

Connects to one CL-2000 and CL-3000 model.

Power output ranges from 15V to 30V. Precise output control is possible in sixteen one-volt increments. A low-to-high feature is also included. For a set period of time after start-up (adjustable to 0, 0.2, 0.4, or 0.6 seconds) the screwdriver will rotate at a slow speed, helping to secure a firm fit between bit and screw and screw and pilot hole.



### Specifications

Model	<b>LHT-30</b>
Input	AC100-240V ±5% (47-63 Hz)
Output Voltage	15V-30V, Volume adjustment
Size (mm)	85x155x42(H)
Weight (kg)	0.37
Power Cord Length (m)	1.8

## LVT-30

RoHS

Connects to one CL-2000 and CL-3000 model.

The LVT-30 is a switching power pack that connects to HIOS power torque/low-torque drivers. It includes controls for low rpm/low torque screw fixing jobs and 16-stage adjustable rpm.

### Specifications


Model	<b>LVT-30</b>
Input	AC100-240V ±5% (47-63 Hz)
Output Voltage	15V-30V, Volume adjustment
Size (mm)	85x155x42(H)
Weight (kg)	0.37
Power Cord Length (m)	1.8



## CLT-100

RoHS CE

Connects to two CL, SS or  $\alpha$  series driver. (except the  $\alpha$ -6500, CL-9000 model).




### Specifications

Model	<b>CLT-100</b>
Input	AC100V, 120V or 220-240V ±5% (50/60 Hz)
Output Voltage	LOW/Hi
Size (mm)	182x145x132 (H)
Weight (kg)	4.0
Power Cord Length (m)	1.8

## MC-70L

RoHS CE

Connects to many CL, SS,  $\alpha$  series drivers.



### Specifications

Model	<b>MC-70L<sup>®</sup></b>	
Input	AC100V, 120V or 220-240V ±5% (50/60 Hz)	
Output Voltage	LOW/Hi	
Size (mm)	320x220x153 (H)	
Weight (kg)	12.0	
Power Cord Length (m)	1.8	
Accessories	Trunk-line wire 20 m 1 line (Black and Red), Branch-line wire 0.5 m 10 lines (Black and Red), U-Element 20 pcs. #560B	
Max. number of drivers	Up to 20	CL-2000, CL-3000, CL-4000, SS-2000, SS-3000, SS-4000
	Up to 10	CL-6000, CL-6500, CL-7000, SS-6500, SS-7000, $\alpha$ -4500, $\alpha$ -5000
	Up to 5	$\alpha$ -6500

## Control box CB-105(SUB)

RoHS

Control boxes for cutting off and supplying current in response to clutch action of drivers. Each driver should be connected to one control box.

### Specifications

Size (mm)	70 x 42 x 100(H)
Weight (g)	240
Input cord Length (m)	2
Attachment Plates	2 pieces



## CLT-75

RoHS CE

Connects to one CL-9000 model.



### Specifications

Model	<b>CLT-75</b>
Input	AC100V, 120V or 220-240V ±5% (50/60 Hz)
Output Voltage	Hi
Size (mm)	182x220x133 (H)
Weight (kg)	6.0
Power Cord Length (m)	1.8

